



EPC-BYT2

Intel® Atom™ SoC processor J1900 Fanless Tiny System

- > Onboard Intel® Celeron® SoC Processor
- > Intel® Valleyview D SoC
- > One 204-pin SODIMM Socket Up to 8GB DDR3L 1333MHz SDRAM
- > Rich I/O, 1 VGA, 1 HDMI, 1 COM/2COM, 2 LAN, 4 USB, 2 Antenna mounting
- > Expansion Slot Supports 2 Mini PCIe Slot
- > Wide Range DC Power Input from 12 ~ 26V
- > Fanless Operating from -10 ~ 45°C
- > Compact Size, 175mm x 110mm x 40mm
- > Optional Wall Mount Kit / VESA / DIN-Rail
- > Supports TPM 1.2 (Factory Option)

+ Spec

System	
Processor	Intel® Celeron® Processor J1900 (2M Cache, up to 2.42 GHz)
System Memory	One 204-pin SODIMM Socket Up to 8GB DDR3L 1333MHz SDRAM
BIOS	AMI uEFI BIOS, 64Mbit SPI Flash ROM
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec./1sec.step
H/W Status Monitor	Monitoring System Temperature, Voltage with Auto Throttling Control
SBC	ECM-BYT2
Expansion	
Expansion	1 x Full Size Mini PCIe (mSATA supported) 1 x Half Size Mini PCIe
Storage	
Storage	1 x mSATA 1 x 2.5" Drive Bay
I/O	
USB	4 x USB (1 x USB 3.0, 3 x USB 2.0)
COM Port	1 x RS-232/2 x RS232 (by order information)
Antenna	2 x Antenna mounting
HDMI	1 X HDMI
VGA	1 x VGA
Switch	1 x Power on/off membrane w/ LED
Display	
Chipset	Intel® HD Graphics
Resolution	VGA Mode: 2560 x 1600 @ 60Hz HDMI Mode: 1920 x 1200 @ 60Hz
Multiple Display	Dual Display
Ethernet	
Chipset	2 x Realtek RTL8111E Gigabit Ethernet
Ethernet Interface	10/100/1000 Base-Tx Gigabit Ethernet Compatible
LAN Port	2 x RJ45
Mechanical & Environmental	
Power Requirement	+12~26Vdc in Lockable DC Jack 2-Pin Terminal Block (Factory Option)
ACPI	Single Power ATX Support S0, S3, S4, S5 ACPI 3.0 Compliant
Power Type	AT/ATX (ATX is the default setting)
Operating Temperature	-10 ~ +45°C (w/mSATA & SSD), Ambient w/Air Flow (Factory Option:-10~+50°C) 0 ~ 40°C (32 ~ 104°F) (w/2.5" Drive Bay), Ambient w/Air Flow
Storage Temperature	-40 ~ 75°C (-40 ~ 167°F)
Weight	960g
IP Rating	40 (Factory Option)
Vibration Protection	With SSD: 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
Shock Protection	With SSD: 10G, IEC 60068-2-27, Half Sine, 11ms
Dimension	175mm x 110mm x 40mm (W x D x H)
Relative Humidity	0% ~ 90% Relative Humidity, Non-condensing
Color	Black
Certifications	
Certification Information	CE, FCC Class A



 Ordering

EPC-BYT2-A2-1R
Intel® Atom™ SoC processor J1900 Fanless Tiny System

EPC-BYT2-A2-2R
Intel® Atom™ SoC processor J1900 w/2COM Fanless Tiny System

ACC-EPC-VESA-04R
VESA 75 Mount Kit VESA Kit

ACC-EPC-VESA-05R
VESA 100 Mount Kit VESA Kit

ACC-EPC-DINRACK-1R
Din Rail Kit