

Physical Parameter

Physical Parameter data

Pixel Pitch	2.0 mm
Pixel Configuration	1 red, 1 green, 1 blue
Configuration (LxH, per cabinet)	120x270 pixels
Diode Type	Surface Mount Device (SMD)
Dimensions (mm, LxHxD, per cabinet)	240x540x81 mm
Diagonal (inch, DiagonalxD, per cabinet)	23.3 inch x 3.18 inch
No. of Modules (WxH, per cabinet)	1 x 3
Weight (per cabinet/per m ²)	3.2Kg / 24.7Kg

Optical Parameter

Optical Parameter data

Brightness ⁽¹⁾	1,200 nit / 600 nit
Contrast Ratio (Peak/Max) ⁽¹⁾	8,000:1
Viewing angle - Horizontal	145°
Viewing angle - Vertical	145°
Bit Depth	16 bit (Internal processing 18bit)
Color Temperature - Default	6,500K
Color temperature - Adjustable	2,800 ~ 10,000K (use S/BOX)

Electrical Parameter

Electrical Parameter

Video Rate	50/60 Hz
Cabinet - Input Power Range	100~240 VAC, 50/60 Hz
Power consumption - Max	463 (W/m ²) / 60 (W/Cabinet)
Power consumption - Typical	154 (W/m ²) / 20 (W/Cabinet)
Heat Generation - Max(BTU/SF) ⁽⁵⁾	1,580 (BTU/m ²) / 205 (BTU/Cabinet)
Heat Generation - Typ (per hour) ⁽⁵⁾	526 (BTU/m ²) / 69 (BTU/Cabinet)
Refresh rate	3,840 Hz

Operation Conditions

Operation Conditions data

Working Temperature / Humidity	0°C~40°C / 10~80%RH
Storage Temperature / Humidity	-20°C~45°C / 5~95%RH
IP Rating	IP20
LED Lifetime	100,000 hours to half brightness

Certification

Certification data

Safety	EMC Class A, Safety 60950-1, FCC, UL, CB, KCC, RoHS
--------	---

Service

Service data

Service	Front
---------	-------

Package

Package data

Box Dimension (WxDxH)	653 x 148 x 354
Box Volume (m3)	0.342
Package Weight (kg, per cabinet)	4.9kg

Special Installation

Special Installation data

Curve (Concave)	3000R
Curve (Convex)	3000R
Rotation	Yes (90 degree clockwise)
L-shape	Yes

Disclaimer

Disclaimer data

Disclaimer⁽¹⁾	Peak Value according to IDMS (Information Display Measurement Standard)
---------------------------------	---