

PANEL

Screen Size	21.5"
Panel Technology	IPS
Aspect Ratio	16 : 9
Native Resolution	1,920 x 1,080 (FHD)
Refresh Rate	60 Hz
Brightness (Typ., cd/m²)	250
Contrast Ratio	1,000 : 1
Viewing Angle (H x V)	178 x 178
Response Time	14ms (G to G)
Surface Treatment (Haze)	25 %
Life Time (Min.)	30,000 Hrs
Operation Hours (Hours / Day)	16 / 7
Portrait / Landscape	No / Yes

CONNECTIVITY

Input	HDMI (2, HDCP2.2), USB 2.0 Type A, Audio In
Output	-
External Control	RS232C In (Phone-jack), RJ45 (LAN) In, IR In

MECHANICAL SPECIFICATION

Bezel Color	Black
Bezel Width	16.3 mm (Even Bezel)
Weight (Head)	3.34 kg
Packed Weight	4.74 kg
Monitor Dimension (W × H × D)	510.3 x 302.1 x 53.8 mm
Carton Dimensions (W × H × D)	565.0 x 357.0 x 103.0 mm
Handle	No
VESA™ Standard Mount Interface	100 x 100 mm

FEATURE

Key Feature	Internal Memory 8GB, Built-in Wi-Fi, Temperature Sensor, Local Key Operation, Embedded CMS (Local Contents Scheduling, Group Manager), USB Plug & Play, Fail Over, Background Image (Booting Logo Image, No Signal Image), PIP, PBP (2), Screen Share, Play via URL, Setting Data Cloning, SNMP, ISM (Image Sticking Minimization) Method, Control Manager, Crestron Connected® (Network based control), Smart Energy Saving, PM Mode, Wake on LAN, Beacon, HDMI-CEC (Compatibility may differ by equipment), SI Server Setting, webRTC, Pro:Idiom
-------------	--

ENVIRONMENT CONDITIONS

Operation Temperature	0°C to 40°C
Operation Humidity	10% to 80%

POWER

Power Supply	AC 100-240 V~, 50 / 60 Hz
--------------	---------------------------

Power Type	Built-In Power
------------	----------------

Power Consumption (Typ. / Max.)	30 W / 33 W
---------------------------------	-------------

Power Consumption (Smart Energy Saving)	15 W ± 5 %
---	------------

SOUND

Speaker	Yes (1 W x 2 ea)
---------	------------------

CERTIFICATION

Safety	CB / NRTL
--------	-----------

EMC	FCC Class "A" / CE
-----	--------------------

ErP	Yes (EU Only)
-----	---------------

ePEAT (US Only)	No
-----------------	----

OPS COMPATIBILITY

OPS Type Compatible	No
---------------------	----

OPS Power Built In	No
--------------------	----

SOFTWARE COMPATIBILITY

Content Management Software	SuperSign CMS
-----------------------------	---------------

Control and Monitoring Software	SuperSign Control / Control+
---------------------------------	------------------------------

ACCESSORY

Basic	Remote Controller, Power Cord, QSG, HDMI Cable, Phone to RS232C Gender, External IR, IR Sheet
-------	---
