

PANEL

|                          |                                                                                                  |
|--------------------------|--------------------------------------------------------------------------------------------------|
| Screen Size              | 43"                                                                                              |
| Panel Technology         | IPS                                                                                              |
| Native Resolution        | 3,840 x 2,160 (UHD)                                                                              |
| Brightness (Typ., nit)   | 350                                                                                              |
| Contrast Ratio           | 1,200:1                                                                                          |
| Dynamic CR               | 500,000 : 1<br>* The luminosity ratio of Full Black / Full White color on video input condition. |
| Color gamut              | BT709 95 %                                                                                       |
| Viewing Angle (H x V)    | 178 x 178                                                                                        |
| Color Depth              | 1.07 Billion Colors (10 bit)                                                                     |
| Response Time            | 8ms (G to G)                                                                                     |
| Surface Treatment (Haze) | Haze 3%                                                                                          |
| Operation Hours          | 18 / 7 (Hours / Day)                                                                             |
| Portrait / Landscape     | Yes / Yes                                                                                        |

CONNECTIVITY

|                  |                                                          |
|------------------|----------------------------------------------------------|
| Input            | HDMI (3, HDCP 2.2/1.4), USB 2.0 Type A                   |
| Output           | Audio                                                    |
| External Control | RS232C (4 Pin Phone Jack) In / Out, RJ45 (LAN) In, IR In |

## MECHANICAL SPECIFICATION

|                                |                         |
|--------------------------------|-------------------------|
| Bezel Color                    | Black                   |
| Bezel Width                    | 9.9mm(T/R/L), 14.4mm(B) |
| Weight (Head)                  | 11.2 kg                 |
| Monitor Dimension (W × H × D)  | 962.5 × 556.8 × 39.9 mm |
| Handle                         | No                      |
| VESA™ Standard Mount Interface | 200 x 200               |

## ENVIRONMENT CONDITIONS

|                       |             |
|-----------------------|-------------|
| Operation Temperature | 0°C to 40°C |
| Operation Humidity    | 10% to 80%  |

## POWER

|              |                              |
|--------------|------------------------------|
| Power Supply | AC 100 - 240 V ~, 50 / 60 Hz |
| Power Type   | Built-In Power               |

## POWER CONSUMPTION

|                            |                                   |
|----------------------------|-----------------------------------|
| Typ. / Max.                | 70W / 105W                        |
| Power off                  | 0.5W                              |
| Smart Energy Saving        | 50W                               |
| DPM                        | 0.5W                              |
| BTU (British Thermal Unit) | 239 BTU/Hr(Typ.), 359 BTU/Hr(Max) |

## SOUND

|         |     |
|---------|-----|
| Speaker | Yes |
|---------|-----|

## CERTIFICATION

|        |           |
|--------|-----------|
| Safety | CB / NRTL |
|--------|-----------|

|     |                         |
|-----|-------------------------|
| EMC | FCC Class "A" / CE / KC |
|-----|-------------------------|

|     |     |
|-----|-----|
| ErP | Yes |
|-----|-----|

## OPS COMPATIBILITY

|                     |    |
|---------------------|----|
| OPS Type Compatible | No |
|---------------------|----|

|                    |     |
|--------------------|-----|
| OPS Power Built In | Yes |
|--------------------|-----|

## SOFTWARE COMPATIBILITY

|               |     |
|---------------|-----|
| SuperSign CMS | Yes |
|---------------|-----|

|                              |     |
|------------------------------|-----|
| SuperSign Control / Control+ | Yes |
|------------------------------|-----|

|              |     |
|--------------|-----|
| SuperSign WB | Yes |
|--------------|-----|

|                        |     |
|------------------------|-----|
| SuperSign Media Editor | Yes |
|------------------------|-----|

## ACCESSORY

|       |                                                                             |
|-------|-----------------------------------------------------------------------------|
| Basic | Remote Controller, Power Cord, QSG, Regulation Book, Phone to RS232C Gender |
|-------|-----------------------------------------------------------------------------|

|          |                                                               |
|----------|---------------------------------------------------------------|
| Optional | Stand(ST-653T), Wall bracket(LSW240B), VESA Adapter(AM-B220S) |
|----------|---------------------------------------------------------------|

## GENERAL

Region

Global

---