

PANEL

Screen Size	55"
Panel Technology	IPS
Aspect Ratio	16 : 9
Native Resolution	1,920 x 1,080 (FHD)
Brightness (Typ., cd/m²)	700
Contrast Ratio	1,200:1
Dynamic CR	500,000 : 1 (The luminosity ratio of Full Black/Full White color on video input condition.)
Viewing Angle (H x V)	178 x 178
Response Time	8 ms (G to G)
Surface Treatment	3%
Life Time (Typ.)	60,000 Hrs
Operation Hours	24 Hrs
Orientation	Landscape & Portrait

CONNECTIVITY

Input	HDMI(2), DP, DVI-D, Audio, USB
Output	DP, Audio
External Control	RS232C In/out, RJ45(LAN) In, IR In

MECHANICAL SPECIFICATION

Bezel Color	Black
Bezel Width	2.25 mm (T/L) / 1.25 mm(B/R)
Monitor Dimension (W × H × D)	1,213.4 x 684.2 x 93.1 mm
Weight (Head)	20.3 kg
Carton Dimensions (W × H × D)	1,353 x 980 x 263 mm
Packed Weight	33 kg
Handle	Yes
VESA™ Standard Mount Interface	600 x 400 mm

ENVIRONMENT CONDITIONS

Operation Temperature	0°C to 40°C
Operation Humidity	10 % to 80 %

POWER

Power Supply	100-240V~, 50/60Hz
Power Type	Built-In Power

POWER CONSUMPTION

Typ./Max	165 W / 195 W
Smart Energy Saving	85 W

CERTIFICATION

Safety	CB / NRTL
--------	-----------

EMC	FCC Class "A" / CE / KC
------------	-------------------------

ErP / Energy Star	Yes (EU Only) / Yes (Energy Star 8.0)
--------------------------	---------------------------------------

MEDIA PLAYER COMPATIBILITY

OPS Type compatible	No
----------------------------	----

SOFTWARE COMPATIBILITY

Content Management Software	SuperSign CMS
------------------------------------	---------------

Control and Monitoring Software	SuperSign Control/Control+
--	----------------------------

ACCESSORY

Basic	Remote Controller, Power Cord, RS232C Cable, DP Cable, IR Receiver, Guide Bracket, Screws, Manual
--------------	---

Optional	Wall mount (Landscape: WM-L640V, Portrait: WM-P640V)
-----------------	--
