

PANEL

Screen Size	55" (54.64" measured diagonal)
Resolution	1,920 x 1,080 (FHD)
Brightness (Typ., cd/m²)	2500

CONNECTIVITY

Input	HDMI(2), DP, DVI-D, Audio, USB
Output	DP, External Speaker (L/R)
External Control	RS232C In/Out, RJ45 In, IR Receiver In

PHYSICAL SPECIFICATION

Bezel Width	12.0 mm (T/B), 9.9 mm (L/R)
Monitor Dimension (W x H x D)	1,235.5 x 709.4 x 85.4 mm
Weight (head)	24.7 kg
Carton Dimensions (W x H x D)	1,360 x 231 x 844mm
Packed Weight	29.9 kg
VESA™ Standard Mount Interface	600 x 400 mm

POWER

Power Type	Built-In Power
Power Supply	100-240V~, 50/60Hz

POWER CONSUMPTION

Typ./Max	240 W / 270 W
Smart Energy Saving	120 W

STANDARD(CERTIFICATION)

Safety	CB / NRTL
EMC	FCC Class "A" / CE / KC / VCCI

SOFTWARE COMPATIBILITY

Content Management Software	SuperSign CMS
Control and Monitoring Software	SuperSign Control+ (Software compatibility may change over time.)

ACCESSORY

Basic	Remote Controller, Power Cord, HDMI Cable, Manual (ESG/EIG), IR Receiver (w/ Ambient Light Sensor)
-------	--