

PANEL

Screen Size	55"
Panel Technology	IPS
Aspect Ratio	16 : 9
Native Resolution	1,920 x 1,080 (FHD)
Dynamic CR	500,000 : 1 (The luminosity ratio of Full Black/Full White color on video input condition.)
Brightness(Typ.,cd/m²)	500
Contrast Ratio	1,200:1
Viewing Angle (H x V)	178 x 178
Response Time	8ms (G to G)
Surface Treatment	3%
Life Time (Typ.)	60,000 Hrs
Operation Hours	24 Hrs
Orientation	Landscape & Portrait

CONNECTIVITY

Input	HDMI(2), DP, DVI-D, Audio, USB
Output	DP, Audio
External Control	RS232C In/out, RJ45(LAN) In, IR In

MECHANICAL SPECIFICATION

Bezel Color	Black
Bezel Width	2.25 mm (T/L) / 1.25 mm(B/R)
Monitor Dimension (W × H × D)	1,213.4 x 684.2 x 93.1 mm
Weight (Head)	20.3 kg
Carton Dimensions (W × H × D)	1,353 x 980 x 263 mm
Packed Weight	33 kg
Handle	Yes
VESA™ Standard Mount Interface	600 x 400 mm

ENVIRONMENT CONDITIONS

Operation Temperature	0°C to 40°C
Operation Humidity	10 % to 80 %

POWER

Power Supply	100-240V~, 50/60Hz
Power Type	Built-In Power

POWER CONSUMPTION

Typ. / Max.	130 W / 150 W
Smart Energy Saving	62 W

CERTIFICATION

Safety	CB / NRTL
--------	-----------

EMCFCC Class "A" / CE / KC

MEDIA PLAYER COMPATIBILITY**OPS Type compatible**No

SOFTWARE COMPATIBILITY**Content Management Software**SuperSign CMS

Control and Monitoring SoftwareSuperSign Control/Control+

ACCESSORY**Basic**Remote Controller, Power Cord, RS232C Cable, DP Cable, IR Receiver, Guide Bracket, Screws, Manual

OptionalWall Mount (Landscape: WM-L640V, Portrait: WM-P640V)
