

PANEL

|                               |                                                                                                |
|-------------------------------|------------------------------------------------------------------------------------------------|
| Screen Size                   | 65"                                                                                            |
| Panel Technology              | IPS                                                                                            |
| Native Resolution             | 3,840 × 2,160 (UHD)                                                                            |
| Brightness (Typ.)             | 500                                                                                            |
| Contrast Ratio                | 1,100:1                                                                                        |
| Dynamic CR                    | 1,000,000 : 1 *The luminosity ratio of Full Black / Full White color on video input condition. |
| Color gamut                   | BT709 95%                                                                                      |
| Viewing Angle (H x V)         | 178 x 178                                                                                      |
| Color Depth                   | 1.07 Billion Colors (10 bit)                                                                   |
| Response Time                 | 8ms(G to G)                                                                                    |
| Surface Treatment             | Haze 28%                                                                                       |
| Operation Hours (Hours / Day) | 24 / 7                                                                                         |
| Portrait / Landscape          | Yes / Yes                                                                                      |

CONNECTIVITY

|                  |                                                                                                           |
|------------------|-----------------------------------------------------------------------------------------------------------|
| Input            | HDMI (2, HDCP 2.2/1.4), HDMI (1, HDCP 1.4), DP (1, HDCP 2.2/1.3), DVI-D (HDCP 1.4), Audio, USB 2.0 Type A |
| Output           | DP, Audio                                                                                                 |
| External Control | RS232C (4 Pin Phone Jack) In / Out, RJ45(LAN) In, IR In                                                   |

## MECHANICAL SPECIFICATION

|                                           |                            |
|-------------------------------------------|----------------------------|
| Bezel Color                               | Black                      |
| Bezel Width                               | 9.9mm(T/R/L), 14.4mm(B)    |
| Weight (Head)                             | 28.2 kg                    |
| Monitor Dimension (W × H × D)             | 1,453.3 × 844.0 × 39.9 mm  |
| Monitor Dimensions with Stand (W × H × D) | 1,453.3 × 893.1 × 290.0 mm |
| Handle                                    | No                         |
| VESA™ Standard Mount Interface            | 300 x 300 mm               |

## SPECIAL FEATURE

|                 |                                                                     |
|-----------------|---------------------------------------------------------------------|
| Tilt (Facedown) | Yes (Max. 30°) *In conditions within 30°C temperature, 50% humidity |
| IP Rating       | IP5x                                                                |

## ENVIRONMENT CONDITIONS

|                       |              |
|-----------------------|--------------|
| Operation Temperature | 0°C to 40°C  |
| Operation Humidity    | 10 % to 80 % |

## POWER

|              |                          |
|--------------|--------------------------|
| Power Supply | AC 100–240 V ~, 50/60 Hz |
| Power Type   | Built-In Power           |

## POWER CONSUMPTION

|             |               |
|-------------|---------------|
| Typ. / Max. | 120 W / 165 W |
|-------------|---------------|

|                            |                                         |
|----------------------------|-----------------------------------------|
| BTU (British Thermal Unit) | 409 BTU/Hr (Typ.),<br>563 BTU/Hr (Max.) |
|----------------------------|-----------------------------------------|

## SOUND

|         |     |
|---------|-----|
| Speaker | Yes |
|---------|-----|

## CERTIFICATION

|        |          |
|--------|----------|
| Safety | CB, NRTL |
|--------|----------|

|     |                         |
|-----|-------------------------|
| EMC | FCC Class "A" / CE / KC |
|-----|-------------------------|

|     |     |
|-----|-----|
| ErP | Yes |
|-----|-----|

## OPS COMPATIBILITY

|                     |     |
|---------------------|-----|
| OPS Type Compatible | Yes |
|---------------------|-----|

|                    |    |
|--------------------|----|
| OPS Power Built In | No |
|--------------------|----|

## SOFTWARE COMPATIBILITY

|               |     |
|---------------|-----|
| SuperSign CMS | Yes |
|---------------|-----|

|                              |     |
|------------------------------|-----|
| SuperSign Control / Control+ | Yes |
|------------------------------|-----|

|              |     |
|--------------|-----|
| SuperSign WB | Yes |
|--------------|-----|

|                        |     |
|------------------------|-----|
| SuperSign Media Editor | Yes |
|------------------------|-----|

## ACCESSORY

|       |                                                                                         |
|-------|-----------------------------------------------------------------------------------------|
| Basic | Remote Controller, Power Cord, QSG, HDMI Cable, Regulation Book, Phone to RS232C Gender |
|-------|-----------------------------------------------------------------------------------------|

---

**Optional**

Stand (ST-653T), Wall Bracket (LSW350B), VESA Adapter (AM-B330S), OPS Kit (KT-OPSF)

---