




ARC-1732

**17" 6th Gen Intel® ULT Core™ Processor i7/i5/i3
Fanless Rugged Touch Panel PC with IET
Expansion**

- > Onboard 6th Gen Intel® ULT Core™ i5 6300U 2.40GHz BGA Processor
- > Full Flat Front Panel with Projected Capacitive Touch Supports Multi Touch
- > One SODIMM sockets supports up to 16GB DDR4 2133 SDRAM
- > 4 USB3.0, 2 COM
- > Dual Intel Gigabit LAN
- > Wide Voltage +12V ~ +26V Input, ErP Power
- > Available Expansion for Audio, USB, COM, HDMI, PCIe, GPIO, CAN Bus
- > IP65 Compliant Front Panel, IP41 Rear Box
- > With Panel Mount kits included
- > TPM 1.2 Function (Optional)

+ Spec

System Information	
Processor	6th Gen Intel® Core™ i5-6300U, 2-Core, 2.4GHz processor
System Memory	1 x 260-Pin DDR4 2133MHz SO-DIMM up to 16 GB
I/O Chipset	EC ITE IT8528E
Watchdog Timer	H/W Reset, 1sec. ~ 65535min. and 1sec. or 1min./step
H/W Status Monitor	Monitoring CPU & System Temperature and Voltage
SBC	ARC-SKLU
Expansion	
Expansion	1 x Mini PCIe Support mSATA 1 x 80-pin IET interface
Storage	
Storage	1 x 2.5" Drive Bay (7mm HDD Restricted)
Panel	
LCD Size	17" SXGA
Display Type	SXGA
Resolution	1280 x 1024
Pixel pitch	0.264mm(H) x 0.264mm(V)
Luminance	350 cd/m²
Contrast ratio	800
Viewing angle	60 (U), 80 (D), 80 (L), 80 (R)
Response time	30 ms
Backlight	TFT-LCD
Touch Type	Projective Capacitive Multi-Touch up to 10 points
Touch Light Transmission	89 %
Touch Controller	USB touch (EETI)
I/O	
USB Port	4 x USB 3.0
COM Port	1 x RS-232/422/485 1 x RS-232
SATA	1 x SATA III
Other	3 x Knockouts for Antenna Mounting
Display	
Graphic Chipset	Intel® Skylake SoC integrated Graphics Supports optional dual display
Spec. & Resolution	HDMI: Max. resolution 4096x2160 @ 24Hz (Optional by IET module)
Audio	
Audio Codec	Realtek ALC888S
Speaker Output	2 x 2W
Certifications	
Certification Information	CE FCC Class B
Ethernet	
LAN Chipset	1 x Intel® I211AT 1 x Intel® I219LM
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	2 x RJ-45
Power Requirement	
DC Input	+12V ~ +26V
DC Input Connector	Lockable DC Jack



Adapter	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A Adapter) AC-DC Adapter
Mechanical & Environmental	
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Weight	5.2 Kgs
Vibration Test	With SSD/mSATA : 1.5Gms, IEC 60068-2-64, Random, 5 ~ 500Hz, 1hr/axis
Shock Test	Operating with SSD/CFast/mSATA : IEC 60068-2-27 Testing procedures, functional shock=20G
IP Rating	Front IP65 Rear IP41
Mounting Kit	Wall / Stand / VESA 75mm x 75mm, 100mm x 100mm Panel Mount with mounting kits
Power Mode	AT/ATX (ATX is default setting)
System Fan	Fanless
Construction - Front	Die Casting with Cover lens
Construction - Rear	Black Die Casting
Dimension	392.5 x 325.1 x 59.5 mm
Software Support	
OS Information	Win 7/10 , Linux
Ordering Information	
Ordering Information	ARC-1732-630-B2-1R 17" 1280x1024 Industrial Touch Panel PC, ErP Design, PCAP Multi Touch 6th Gen Intel Core i5 6300U 2.4GHz CPU/2GLAN/2COM/4USB/SPK/12~26V input/12V Adapter Optional IET Module list: ACC-ARC-USB-1R 4 x USB 3.0 Kit for ARC Series ACC-ARC-AUDIO-1R HDMI + 5.1 CH Audio Kit for ARC Series ACC-ARC-MPCIE-1R HDMI + MPCIE w/SIM Kit for ARC Series ACC-ARC-COM-1R 2 x Isolated RS-232 Kit for ARC Series ACC-ARC-COM-2R 3 x RS-232 Kit for ARC Series ACC-ARC-COM-3R 2 x RS-232 + USB Kit for ARC Series ACC-ARC-COM-4R 2 x RS-232 + LAN Kit for ARC Series ACC-ARC-GPIO-1R 12-bit GPIO + 2-pin CAN Bus Kit for ARC Series ACC-ARC-OBDDI-1R OBDDI - CAN Bus Kit for ARC Series (OBDDI/EOBD for Small Vehicle) ACC-ARC-OBDDI-2R OBDDI - CAN Bus Kit for ARC Series (J1939J1708 for Large Vehicle) ACC-ARC-OBDDI-3R OBDDI - CAN Bus Kit for ARC Series (ISO15765-4 for Special Large Vehicle)