

T(P)GS-L5016T

16 10/100/1000T (w/8/16 PoE at/af) EN50155 OS3 Managed Ethernet Switch w/ Enhanced G.8032 Ring; PXE; 24V/WVI input

- Total 16 Port GT Ethernet Switch
- PoE model: w/8/16 PoE ports
- PoE model: Support IEEE802.3at/af up to 30W per port; PoE management incl. Detection and Scheduling
- Support PXE to verify switch firmware with the latest or certain version on server
- Enhanced G.8032 ring protection < 20ms for single ring. Supports enhanced mode and basic mode; Enhanced G.8032 ring covers multicast packets; MSTP 8 MSTI /RSTP ; support MRP ring
- Miss-wiring avoidance & node failure protection
- User friendly UI, including auto topology drawing; Complete CLI
- Support LACP link aggregation, IGMP v3/router port, MLD snooping, DHCP server & DHCP Option82; Port based DHCP distribution, DHCP Snooping, Mac based DHCP server, SSH v2/SSL, HTTPS, INGRESS ACL L2/L3, TACACS+, QinQ, QoS by VLAN
- Protocol based VLAN; IPv4 Subnet based VLAN
- Enhanced Environmental Monitoring for temp., actual input voltage, current & total power load
- IP54/IP67 Aluminum housing for best heat dissipation and preventing moist ingress
- USB port to upload & download the configuration file
- Dual power input 16.8V~137.5V with galvanic isolation between input power, PoE and system
- Factory reset pin to restore to factory default setting
- Inrush current protection
- Optional L3Lite or IEC 61375-2-5 TBN features to be upgradable
- Wide range operation temperature :-40~70C/-40~158F



OVERVIEW

Lantech T(P)GS-L5016T is a high performance OS3 (All Gigabit) Ethernet switch with 16 10/100/1000T. PoE model has 8(16) PoE 802.3af/at ports which provides advanced security function for network aggregation deployment.

It delivers ITU G.8032 enhanced ring recovery less than 20ms in single ring. The QoS, advanced security including INGRESS ACL L2/L3, TACACS+, SSH v2/SSL and Mac based DHCP server, DHCP Option 82, DHCP server, IGMPv1/v2/v3/router port are supported and also required in large network. It also supports 10K Jumbo frames.

Up to 8/16 PoE at/af ports w/advanced PoE management

Compliant with 802.3af/at standard, the Lantech TPGS-L5016T is able to feed each PoE port up to 30 Watt at each PoE port for various IP PD devices. Lantech TPGS-L5016T supports advanced PoE management including PoE detection and scheduling. PoE detection can detect if the connected PD hangs then restart the PD; PoE scheduling is to allow pre-set power feeding schedule upon routine time table. Each PoE port can be Enabled/disabled, get the voltage, current, Watt, and temperature info displayed on WebUI.

Dual WVI input with max PoE budget and Inrush current

protection

The T(P)GS-L5016T WVI model accepts 16.8~137.5VDC dual input with galvanic isolation and PoE model can feed 54V output for PoE feeding with 80W budget. The inrush current on initial power up can be limited lower than 10 x nominal current.

Support PXE to verify switch firmware with the latest or certain version

The switch can check its firmware version during booting time via PXE protocol. If switch finds any newer version, it will upload automatically.

Miss-wiring avoidance, Node failure protection, Loop protection

The T(P)GS-L5016T is also embedded with several features for stronger and reliable network protection in an easy and intuitive way. When the pre-set ring configuration failed or looped by miss-wiring, Lantech T(P)GS-L5016T is able to send alert with the LED indicator and disable ring automatically.

Node failure protection ensures the switches in a ring to survive after power breakout is back. The status can be shown in NMS when each switch is back. This feature prevents the broken

ring and keep ring alive without any re-configuration needed.

Loop protection is also available to prevent the generation of broadcast storm when a dumb switch is inserted in a closed loop connection.

DHCP option 82 & Port based, Mac based DHCP, Option66, DHCP Snooping, IPv6 DHCP server

DHCP server can assign dedicated IP address by MAC or by port (Port based for single switch), it also can assign IP address by port for multiple switches with single DHCP option82 server. DHCP Snooping is supported. DHCP Option66 server can offer IP address of TFTP server to DHCP client for VOIP application. Basic IPv6 DHCP service can be supported.

User friendly GUI, Auto topology drawing

The user friendly UI, innovative auto topology drawing and topology demo makes T(P)GS-L5016T much easier to get hands-on. The complete CLI enables professional engineer to configure setting by command line.

Built-in IEC 61375-3-4 ECN (Ethernet Consist Network) to work with IEC61375-2-5 TBN

Lantech OS3 Ethernet switches comply with IEC 61375-3-4 (ECN) standard. The support of Ethernet Consist Network allows interconnection between end devices located in single consist of train and interoperability with IEC61375-2-5 (TBN).

Enhanced Storm control

Storm control prevents traffic on a LAN from being disrupted by a broadcast, multicast, or unicast storm on one of the physical interfaces and the detection is more precise and reaction is more efficient.

Optional L3Lite/L3*/ETBN to be upgradable

Lantech OS3 are optional upgradable to L3 Lite/ L3* or ETBN communication protocols for future expansion. The optional L3Lite includes editable routing table, VRRP, Router-on-a-stick, Inter- VLAN routing. Optional ETBN complies with IEC61375-2-5 ETBN for Train Backbone Network.

QinQ, QoS and GVRP supported

It supports the QinQ, QoS and GVRP for large VLAN segmentation.

Enhanced G.8032 ring, 8 MSTI MSTP; MRP ring

Lantech T(P)GS-L5016T features enhanced G.8032 ring which can be self-healed in less than 20ms for single ring topology protection covering multicast packets. It also supports various ring topologies that covers enhanced ring and basic ring by easy setup than others. It supports MSTP that allows RSTP over VLAN for redundant links with 8 MSTI. MRP (Media Redundancy Protocol) can be supported for industrial automation networks.

IGMPv3, GMRP, router port, MLD Snooping, static multicast forwarding and multicast Ring protection

The unique multicast protection under enhanced G.8032 ring can offer immediate self-recovery instead of waiting for IGMP table timeout. It also supports IGMPv3, GMRP, router port, MLD snooping and static multicast forwarding binding by ports for video surveillance application.

802.1X security by MAC address

MAC-based port authentication is an alternative approach to

802.1x for authenticating hosts connected to a port. By authenticating based on the host's source MAC address, the host is not required to run a user for the 802.1x protocol. The RADIUS server that performs the authentication will inform the switch if this MAC can be registered in the MAC address table of switch.

Editable configuration file; USB port for upload/download the configuration

The configuration file of Lantech T(P)GS-L5016T can be exported and edited with word processor for the following switches to configure with ease. The factory reset button can restore the setting back to factory default and built-in watchdog design can automatically reboot the switch when CPU is found dead.

The USB port can upload/download the configuration from/to USB dongle.

Event log & message; 2 DI + 2DO

In case of event, the T(P)GS-L5016T is able to send an email** to pre-defined addresses as well as SNMP Traps out immediately. It provides 2DI and 2DO. When disconnection of the specific port was detected; DO will activate the signal LED to alarm. DI can integrate the sensors for events and DO will trigger the outside alarm and switch will send alert information to IP network with email and traps.

Enhanced environmental monitoring for switch inside information

The enhanced environmental monitoring can detect switch overall temperature, total power load, actual input voltage and current. It also can send the SNMP traps and email** when abnormal.

Protocol based VLAN; Subnet based VLAN

The protocol-based VLAN processes traffic based on protocol. It filters IP traffic from nearby end-stations using a particular protocol such as IP, IPX, ARP or other Ethernet-types in a Hex value. Subnet based VLANs group traffics into logical VLANs based on the source IP address and IP subnet.

The above features can help to build VLAN in the network mixed with managed and un-managed switch as to define packets to which VLAN group based on protocol or subnet.

High reliability and extended working temperature

Lantech T(P)GS-L5016T provides $\pm 2000V$ EFT and $\pm 6000V$ ESD protection, which can reduce unstable situation caused by power line and Ethernet. It has high reliability and robustness coping with extensive EMI/RFI phenomenon, environmental vibration and shocks usually found in Automation, transportation, Wireless backhaul, Semi-conductor factory and assembly lines.


EN50155, EN45545-2, EN61373 verification; High ESD protection

T(P)GS-L5016T passed tests under extensive Industrial EMI and Safety standards. With EN45545-2 Fire & Smoke, EN50155 verification, the T(P)GS-L5016T is best switch for railway on-board/track side, vehicle and mining applications. For more usage flexibilities, T(P)GS-L5016T supports wide operating temperature from $-40^{\circ}C$ to $70^{\circ}C$. ($85^{\circ}C$ operation for 10min.)

FEATURES & BENEFITS

- 16 10/100/1000T Ethernet Switch (Total 16 Ports Switch)
- PoE model: w/8/16 PoE 802.3af/at ports to feed power up to 30W for active mode operation (PoE budget 80W)
- Dual WVI input (16.8V~137.5VDC)
- PoE model: PoE management including PoE detection and scheduling for PD (power devices)
- Back-plane (Switching Fabric):32Gbps
- 16K MAC address table
- 10KB Jumbo frame
- User friendly UI, auto topology drawing, topology demo, complete CLI for professional setting
- Enhanced G.8032 Ring protection in 20ms for single ring
 - Support various ring/chain topologies, including enhanced ring, basic ring
 - Cover multicast and data packets protection
- Supports IEEE 802.1p Class of Service, per port provides 8 priority queues Port base, Tag Base and Type of Service Priority
- IEEE 802.1d STP, IEEE 802.1w RSTP, 802.1s MSTP VLAN redundancy with 8 MSTI
- 4K 802.1Q VLAN, Port based VLAN, GVRP, QinQ, QoS
- Supports IEEE 802.1ab LLDP, Cisco CDP; LLDP info can be viewed via Web/ Console
- Support PXE to verify switch firmware with the latest or certain version
- DHCP server / client / DHCP Option 82 relay / DHCP Option 82 server; Port based DHCP server; DHCP Option 66; DHCP Snooping, Basic IPv6 DHCP server
- Mac based DHCP server to assign IP address
- Bandwidth Control
 - Ingress packet filter and egress* rate limit
 - Broadcast/multicast packet filter control
- Miss-wiring avoidance
 - LED indicator
- Node failure protection
 - Ensure the switches in a ring to survive after power breakout is back
 - The status can be shown in NMS when each switch is back
- System Event Log, SMTP** alert and SNMP Trap for alarm support
- Security
 - SSL/SSH v2/INGRESS ACL L2/L3
 - MAC address table: MAC address entries/Filter/static MAC-Port binding
 - Remote Admin: IP address security management to prevent unauthorized intruder.
 - TACACS+
 - Login Security: IEEE802.1X/RADIUS
 - HTTPS for secure access to the web interface
- Static multicast forwarding forward reversed IGMP flow with multicast packets binding with ports for IP surveillance application
- IGMP router port for multicast protection
- IGMPv1,v2,v3 with Query mode for multi media
- Dual image firmware support
- MLD Snooping for IPv6 Multicast stream
- Enhanced Storm Control
- Supports 2DI/2DO (Digital Input/Digital Output)
- Factory reset pin to restore setting to factory default
- Watchdog design to auto reboot switch when CPU is found dead
- Enhanced environmental monitoring for system actual input voltage, current, ambient temperature and total power load
- Configuration backup and restoration
 - Supports editable configuration file for system quick installation
 - USB port for upload/download the configuration file
- TFTP/HTTP firmware upgrade
- Wide operation temperature: -40C~70C/-40F~158F (85°C operation for 10min.)
- Dual WVI input from 16.8V~137.5VDC
- Dual 24V input from 12V~56VDC
- Galvanic isolation from power input/Ethernet ports to system 1.5KV
- Subnet VLAN and protocol VLAN
- EN45545-2 Fire & Smoke, EN50155 and EN61373 shock/vibration verification
- Diagnostic including Ping / ARP table / DDM information
- Optional L3Lite/L3*/ETBN to be upgradable
- Built-in IEC 61375-3-4 ECN (Ethernet Consistent Network) to work with IEC61375-2-5 TBN
- IP54/IP67 aluminum housing with wall mount design


DIMENSIONS (unit=mm)



SPECIFICATION

Hardware Specification

Standards	IEEE802.3 10Base-T Ethernet IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T IEEE802.3z Gigabit fiber IEEE802.3x Flow Control and Back Pressure IEEE802.3ad Port trunk with LACP IEEE802.1d Spanning Tree IEEE802.1w Rapid Spanning Tree IEEE802.1s Multiple Spanning Tree IEEE802.3ad Link Aggregation Control Protocol (LACP) IEEE802.1AB Link Layer Discovery Protocol (LLDP) IEEE802.1X User Authentication (Radius) IEEE802.1p Class of Service IEEE802.1Q VLAN Tag IEEE802.3at/af Power over Ethernet
Switch Architecture	Back-plane (Switching Fabric): 32Gbps
Mac Address	16K MAC address table
Jumbo frame	10KB
Connectors	10/100/1000T: 16 x M12 8-pole X-coded with Auto MDI/MDI function Power Input connector: 1 x M12 4-pole A-coded Reset/Console/USB : 1 x M12 8-pole A-coded DIDO: 1 x M12 5-pole A-coded
Network Cable	10Base-T: 2-pair STP Cat. 3, 4, 5/ 5E/ 6 cable EIA/TIA-568 100-ohm (100m) 100Base-TX: 2-pair STP Cat. 5/ 5E/ 6 cable; EIA/TIA-568 100-ohm (100m) 1000Base-T: 4-pair STP Cat5E/6 cable
LED	Per unit: Power 1 (Green), Power 2 (Green), FAULT (Red); RM(Green) 10/100/1000T Ethernet port: Link/Activity (Green) PoE : Link/Act (Green) (PoE model)
DI/DO	2 Digital Input (DI) : Level 0: -30~2V / Level 1: 10~30V Max. input current:8mA 2 Digital Output(DO): Open collector to 80 VDC, 50mA
Operating Humidity	5% ~ 95% (Non-condensing)
Operating	-40°C~70°C / -40°F~158°F (85°C operation for

Temperature	10min.)											
Storage Temperature	-40°C~85°C / -40°F~185°F											
Power Supply	Dual DC input, 16.8VDC~137.5VDC											
PoE Budget (PoE model)	<table><tr><td>Input Range</td><td>Power Input</td><td>Maximal PoE Budget</td></tr><tr><td>16.8~27VDC</td><td>Dual Power Input</td><td>80W</td></tr><tr><td>28~137.5VDC</td><td>Single Power Input</td><td>80W</td></tr></table> Higher PoE budget can be applied upon request. **			Input Range	Power Input	Maximal PoE Budget	16.8~27VDC	Dual Power Input	80W	28~137.5VDC	Single Power Input	80W
Input Range	Power Input	Maximal PoE Budget										
16.8~27VDC	Dual Power Input	80W										
28~137.5VDC	Single Power Input	80W										
PoE pin assignment (PoE model)	M12 port #1~#8/16 (-8/-16 model) ; support IEEE 802.3at/af End-point. Per port provides up to 30W 10/100/1000T  1:TXD1+ 5:BD4+ 2:TXD1- 6:BD4- 3:RXD2+ 7:BD3- 4:RXD2- 8:BD3+											
Power Consumption	Max. 33.8W (exclude PoE load)											
Case Dimension	IP54/IP67 model: Aluminum case 304mm(W)x195mm(H)x89.5mm(D)											
Weight	1.8kgs											
Installation	Wall Mount Design											
EMI & EMS	FCC Part 15 Class A EN61000-6-2 EN61000-6-4 CE EN55032 Class A CE EN55024 CE EN61000-4-2 (ESD) Level 3 CE EN61000-4-3 (RS) Level 3 CE EN61000-4-4 (EFT) Level 3 CE EN61000-4-5 ED3 (Surge) Level 3 CE EN61000-4-6 (CS) Level 3 CE EN61000-4-8 (Magnetic field) Level 3 BS EN61000-4-2, BS EN61000-4-3, BS EN61000-4-4, BS EN61000-4-5, BS EN61000-4-6, BS EN61000-4-8, BS EN55032, BS EN55024											
Verifications	EN50155/EN50121-3-2/EN50121-4;											

	EN45545-1, EN 45545-2 Fire & Smoke verification
Stability Testing	EN61373 (Shock and Vibration)
MTBF	551,745 hrs. (IEC 62380 standards)
Warranty	5 years
Software Specification	
Management	SNMP v1 v2c, v3/ Web/Telnet/CLI
SNMP MIB	RFC 1213 MIBII RFC 1158 MIB RFC 1157 SNMP MIB, RFC 2674 Q-Bridge MIB* RFC 1573 IF MIB RFC 2674 Q-Bridge MIB*; Bridge MIB, RFC 2819 RMON MIB Private MIB
ITU G.8032	Support ITU G.8032 for Ring protection in less than 20ms for self-heal recovery (single ring) Support various ring/chain topologies Includes basic single ring, enhanced ring Cover multicast & data packets protection
PoE Management (PoE model)	PoE Detection to check if PD hangs then restart the PD PoE scheduling
Per Port PoE Status (PoE model)	On/ Off, voltage, current, watts, temperature
User friendly UI	■ Auto topology drawing ■ Topology demo ■ Complete CLI for professional setting
Port Trunk with LACP	LACP Port Trunk: 8 Trunk groups
LLDP	Supports LLDP to allow switch to advise its identification and capability on the LAN
CDP	Cisco Discovery Protocol for topology mapping
Enhanced Environmental Monitoring	System status for actual input voltage, current , total power load and ambient temperature to be shown in GUI and send alerting if any abnormal status
VLAN	Port Based VLAN IEEE 802.1Q Tag VLAN (256 entries)/ VLAN ID (Up to 4K, VLAN ID can be assigned from 1 to 4096) GVRP, QinQ, QoS Protocol based VLAN IPv4 Subnet based VLAN
Spanning Tree	Supports IEEE802.1d Spanning Tree and IEEE802.1w Rapid Spanning Tree, IEEE802.1s Multiple Spanning Tree 8 MSTI
Quality of Service	The quality of service determined by port, Tag and IPv4 Type of service, IPv4 Differentiated Services Code Points – DSCP
Class of Service	Support IEEE802.1p class of service, per port provides 8 priority queues
Remote Admin	Supports 10 IP addresses that have permission to access the switch management and to prevent unauthorized intruder.
Login Security	Supports IEEE802.1X Authentication/RADIUS
Port Mirror	Support 3 mirroring types: "RX, TX and Both packet"
Network Security	Support 10 IP addresses that have permission to access the switch management and to prevent unauthorized intruder. 802.1X access control for port based and MAC based authentication/static MAC-Port binding Ingress ACL L2/L3 SSL/SSH v2 for Management HTTPS for secure access to the web interface TACACS+ for Authentication
MLD Snooping	Support IPv6 Multicast stream

IGMP	Support IGMP snooping v1,v2,v3; Supports IGMP static forwarding; 1024 multicast groups; IGMP router port ; IGMP query; GMRP
Static multicast forwarding	Static multicast forwarding forward reversed IGMP flow with multicast packets binding with ports for IP surveillance application
Bandwidth Control	Support ingress packet filter and egress* packet limit. The egress* rate control supports all of packet type. Ingress filter packet type combination rules are Broadcast/Multicast/Flooded Unicast packet, Broadcast/Multicast packet, Broadcast packet only and all types of packet. The packet filter rate can be set an accurate value through the pull-down menu for the ingress packet filter and the egress* packet limit.
Flow Control	Supports Flow Control for Full-duplex and Back Pressure for Half-duplex
Enhanced Storm Control	prevents traffic on a LAN from being disrupted by a broadcast, multicast, or unicast storm on one of the physical interfaces
System Log	Supports System log record and remote system log server
Protection	■ Miss-wiring avoidance ■ Node failure protection ■ Loop protection
SNMP Trap	Up to 5 trap stations; trap types including: ● Device cold start ● Authorization failure ● Port link up/link down ● DI/DO open/close ● Typology change(ITU ring) ● Power failure ● Environmental abnormal
PXE	PXE to verify switch firmware with the latest or certain version
DHCP	Provide DHCP Client/ DHCP Server/DHCP Option 82/Port based DHCP; DHCP Snooping, DHCP Option 66 ; Basic IPv6 DHCP server
Mac based DHCP Server	Assign IP address by Mac that can include dumb switch in DHCP network
DNS	Provide DNS client feature and can set Primary and Secondary DNS server.
NTP/SNTP	Supports NTP/SNTP to synchronize system clock in Internet
Firmware Update	Supports TFTP firmware update, TFTP backup and restore; HTTP firmware upgrade
Configuration upload and download	Supports editable configuration file for system quick installation; Support factory reset pin to restore all settings back to factory default
ECN	Complies with IEC 61375-3-4 (ECN) standard. The support of Ethernet Consist Network allows interconnection between end devices located in single consist of train and interoperability with IEC61375-2-5 (TBN).
Optional L3Lite/L3*/ETBN **	Lantech OS3 are optional upgradable to L3 Lite/ L3* or ETBN communication protocols for future expansion. The optional L3Lite includes editable routing table, VRRP, Router-on-a-stick, Inter-VLAN routing. Optional ETBN complies with IEC61375-2-5 ETBN for Train Backbone Network. Detail SPEC upon request.
Diagnostic	Support Ping, ARP table and DDM information
Dual Image Firmware	Support dual image firmware function

*Future release

**Optional

ORDERING INFORMATION

All model packages include M12 caps and wall mount bracket. All standard models are non-coating, optional coating models are available with -C model name.

- **TPGS-L5016T-8-54-WVI.....P/N:8361-4312**
16 10/100/1000T M12 X-coded; w/8 PoE at/af EN50155 OS3 PoE Managed Ethernet Switch; 16.8V~137.5VDC dual input ; -40~70C/-40~158F ; IP54 housing w/ PoE galvanic isolation
- **TPGS-L5016T-16-54-WVI.....P/N:8361-431**
16 10/100/1000T M12 X-coded; w/16 PoE at/af EN50155 OS3 PoE Managed Ethernet Switch; 16.8V~137.5VDC dual input ; -40~70C/-40~158F ; IP54 housing w/ PoE galvanic isolation
- **TPGS-L5016T-8-54-24V.....P/N:8361-4317**
16 10/100/1000T M12 X-coded; w/8 PoE at/af EN50155 OS3 PoE Managed Ethernet Switch; 12V~56V dual input; -40~70C/-40~158F ; IP54 housing
- **TPGS-L5016T-16-54-24V.....P/N:8361-4318**
16 10/100/1000T M12 X-coded; w/16 PoE at/af EN50155 OS3 PoE Managed Ethernet Switch; 12V~56V dual input ; -40~70C/-40~158F ; IP54 housing
- **TGS-L5016T-54-WVI.....P/N:8361-4311**
16 10/100/1000T M12 X-coded; EN50155 OS3 Managed Ethernet Switch; 16.8V~137.5VDC dual input ; -40~70C/-40~158F ; IP54 housing w/ galvanic isolation
- **TGS-L5016T-54-24V.....P/N:8361-4319**
16 10/100/1000T M12 X-coded; EN50155 OS3 Managed Ethernet Switch; 12V~56V dual input; -40~70C/-40~158F ; IP54 housing
- **TPGS-L5016T-8-67-WVI.....P/N:8361-43122**
16 10/100/1000T M12 X-coded; w/8 PoE at/af EN50155 OS3 PoE Managed Ethernet Switch; 16.8V~137.5VDC dual input ; -40~70C/-40~158F ; IP67 housing w/ PoE galvanic isolation
- **TPGS-L5016T-16-67-WVI.....P/N:8361-43102**
16 10/100/1000T M12 X-coded; w/16 PoE at/af EN50155 OS3 PoE Managed Ethernet Switch; 16.8V~137.5VDC dual input ; -40~70C/-40~158F ; IP67 housing w/ PoE galvanic isolation
- **TPGS-L5016T-8-67-24V.....P/N:8361-43172**
16 10/100/1000T M12 X-coded; w/8 PoE at/af EN50155 OS3 PoE Managed Ethernet Switch; 12V~56V dual input; -40~70C/-40~158F ; IP67 housing
- **TPGS-L5016T-16-67-24V.....P/N:8361-43182**
16 10/100/1000T M12 X-coded; w/16 PoE at/af EN50155 OS3 PoE Managed Ethernet Switch; 12V~56V dual input ; -40~70C/-40~158F ; IP67 housing
- **TGS-L5016T-67-WVI.....P/N:8361-43112**
16 10/100/1000T M12 X-coded; EN50155 OS3 Managed Ethernet Switch; 16.8V~137.5VDC dual input ; -40~70C/-40~158F ; IP67 housing w/ galvanic isolation
- **TGS-L5016T-67-24V.....P/N:8361-43192**
16 10/100/1000T M12 X-coded; EN50155 OS3 Managed Ethernet Switch; 12V~56V dual input; -40~70C/-40~158F ; IP67 housing

OPTIONAL ACCESSORIES

Software package

- **OS3 – L3L P/N: 9000-114**
OS3 software platform with Layer 3 Lite functions (please check Lantech software data sheet for details)
- **OS3 – IEC61375-2-5 P/N: 9000-115**
OS3 software platform with IEC-61375-2-5 ETBN (Ethernet Train Backbone Networks) function (please check Lantech software data sheet for details)
- **OS3 – L3*..... P/N: 9000-116**
OS3 software platform with Layer 3 functions incl. L3L (please check Lantech software data sheet for details)

M12 Connector & Cable

Connector

- **ECONM12-04A(F)-C-180** 4 pin M12 (Female) A-coded 180 degree crimp type connector for power supply
- **ECONM12-08A(M)-180** 8 pin M12 (Male) A-coded 180 degree crimp type connector for reset/console/USB
- **ECONM12-05A(M)-C-180** 5 pin M12 (Male) A-coded 180 degree crimp type connector for DI/DO
- **ECONM12-08X(M)-SPEEDCON** 8 pin M12 (Male) X-coded 180 degree crimp type connector for data, Ethernet CAT6A (10G), shielded, SPEEDCON

Cable

- **ECONM12-4P(F)1.5M CABLE** 4 pin M12 (Female) A-coded 90 degree cable for power supply, 150cm
- **ECONM12-08M2-CONSOLE** 8 pin M12 (Male) A-coded 180 degree to RS232 cable for console, 150cm
- **ECABM12X83MSTP** 8 pin M12 (Male) X-coded 180 degree RJ45 STP cable for data, shielded, 300cm

Others

■ M12 to USB interface adapter	8 pin M12 (Male) A-coded 180 degree M12 to USB 2.0 interface adapter, 8cm
■ USB 2.0 Ethernet Adapter	USB 2.0 to RJ45 Ethernet Adapter
■ ECONM12-08(M) TO DB9+USB2.0-1.5M CABLE	8 pin M12 (Male) A-coded 180 degree M12 to USB2.0 to DB9 (Female) cable, 150cm

Lantech Communications Global Inc.

www.lantechcom.tw
info@lantechcom.tw

© 2022 Copyright Lantech Communications Global Inc. all rights reserved.
The revise authority rights of product specifications belong to Lantech Communications Global Inc.
In a continuing effort to improve and advance technology, product specifications are subject to change without notice.