

# T(P)GS-R5408MGT

8 10/100/1000T + 4 1G/2.5G Copper M12 X-coded (w/8/10 PoE at/af)

EN50155 OS4 Managed Ethernet Switch w/ Enhanced G.8032 Ring,

PXE; WVI input

- Total 8 10/100/1000T + 4 1G/2.5G Copper M12 X-coded
- PoE model: w/8/10 (incl.8 copper + 2 uplink 1G/2.5G copper) PoE Ports
- PoE model: Support IEEE802.3at/af up to 30W per port PoE management incl. Detection and Scheduling
- Enhanced G.8032 ring protection < 20ms for single ring. Supports enhanced mode and basic mode; Enhanced G.8032 ring covers multicast packets; MSTP 8 MSTI /RSTP; support MRP ring
- Miss-wiring avoidance & node failure protection
- User friendly UI, including auto topology drawing ; Complete CLI
- Support LACP link aggregation, IGMP v3/router port, MLD snooping, DHCP server & DHCP Option82; DHCP Snooping, Port based DHCP distribution, Mac based DHCP server, QoS by VLAN, SSH v2/SSL, HTTPS, INGRESS ACL L2/L3, TACACS+, QinQ
- Protocol based VLAN ; IPv4 Subnet based VLAN
- Support PXE to verify switch firmware with the latest or certain version on server
- Enhanced Environmental Monitoring for temp., actual input voltage, current & total power load
- Optional smart bypass 1G/2.5G ports in case of power failure, CPU hang (Up to two pairs)
- IP54/IP67 aluminum enclosure
- Optional L3Lite or IEC 61375-2-5 TBN features to be upgradable
- USB port to upload & download the configuration file
- Dual power input 16.8V~137.5V with galvanic isolation between input power , POE and system
- Factory reset pin to restore to factory default setting
- Inrush current protection
- Wide range operation temperature :-40~70C/-40~158F



## OVERVIEW

Lantech T(P)GS-R5408MGT is a high performance OS4 Ethernet switch with 8 10/100/1000T + 4 1G/2.5G Copper M12 X-Coded with 8/10 (incl.8 copper + 2 uplink 1G/2.5G copper) PoE 802.3af/at ports which provides advanced security function for network aggregation deployment. It delivers ITU G.8032 enhanced ring recovery less than 20ms in single ring while also supports enhanced mode with easy configuration. The comprehensive QoS, advanced security including INGRESS ACL L2/L3, TACACS+, SSH v2/SSL and subnet VLAN, protocol VLAN and Mac based DHCP server, DHCP Option 82, DHCP server, IGMPv1/v2/v3/router port are supported and also required in large network. It also supports 10K Jumbo frames.

### Miss-wiring avoidance, node failure protection, Loop protection

The T(P)GS-R5408MGT also embedded several features for strong and reliable network protection in an easy and intuitive way. When the pre-set ring configuration failed or looped by miss-wiring, Lantech T(P)GS-R5408MGT is able to alert with the LED indicator and disable ring automatically.

Node failure protection ensures the switches in a ring to survive after power breakout is back. The status can be shown in NMS when each switch is back.

Loop protection is also available to prevent the generation of broadcast storm when a dumb switch is inserted in a closed loop connection.

### Support PXE to verify switch firmware with the latest or certain version

The switch can check its firmware version during booting time via PXE protocol. If switch finds any newer version, it will upload automatically.

### DHCP option 82 & Port based, Mac based DHCP, Option66, DHCP Snooping, IPv6 DHCP server

DHCP server can assign dedicated IP address by MAC or by port (Port based for single switch), it also can assign IP address by port for multiple switches with single DHCP option82 server. DHCP Snooping is supported. DHCP Option66 server can offer IP address of TFTP server to DHCP

client for VOIP application. Basic IPv6 DHCP service can be supported.

#### **User friendly GUI, Auto topology drawing**

The user friendly UI, innovative auto topology drawing and topology demo makes T(P)GS-R5408MGT much easier to get hands-on. The complete CLI enables professional engineer to configure setting by command line.

#### **Enhanced G.8032 ring, 8 MSTI MSTP; MRP ring**

Lantech T(P)GS-R5408MGT features enhanced G.8032 ring which can be self-healed in less than 20ms for single ring topology protection covering multicast packets. It also supports various ring topologies that covers enhanced ring and basic ring by easy setup than others. It supports MSTP that allows RSTP over VLAN for redundant links with 8 MSTI. MRP (Media Redundancy Protocol) can be supported for industrial automation networks.

#### **Built-in IEC 61375-3-4 ECN (Ethernet Consist Network) to work with IEC61375-2-5 TBN**

Lantech OS4 Ethernet switches comply with IEC 61375-3-4 (ECN) standard. The support of Ethernet Consist Network allows interconnection between end devices located in single consist of train and interoperability with IEC61375-2-5 (TBN).

#### **Enhanced Storm Control**

Storm control prevents traffic on a LAN from being disrupted by a broadcast, multicast, or unicast storm on one of the physical interfaces and the detection is more precise and reaction is more efficient.

#### **Optional L3Lite/L3\*/ETBN to be upgradable**

Lantech OS4 are optional upgradable to L3 Lite/ L3\* or ETBN communication protocols for future expansion. The optional L3Lite includes editable routing table, VRRP, Router-on-a-stick, Inter- VLAN routing. Optional ETBN complies with IEC61375-2-5 ETBN for Train Backbone Network.

#### **Up to 8/10 (at) PoE at/af ports w/advanced PoE management**

Compliant with 802.3af/at standard, the Lantech TPGS-R5408MGT is able to feed each PoE port up to 30 Watt at each PoE port for various IP PD devices. Lantech TPGS-R5408MGT supports advanced PoE management including PoE detection and scheduling. PoE detection can detect if the connected PD hangs then restart the PD; PoE scheduling is to allow pre-set power feeding schedule upon routine time table. Each PoE port can be Enabled/disabled, get the voltage, current, Watt, and temperature info displayed on WebUI.

#### **QinQ, QoS and GVRP supported**

It supports the QinQ, QoS and GVRP for large VLAN segmentation.

#### **IGMPv3, GMRP, router port, MLD Snooping, static multicast forwarding and multicast Ring protection**

The unique multicast protection under enhanced G.8032 ring can offer immediate self-recovery instead of waiting for IGMP table timeout. It also supports IGMPv3, GMRP, router port, MLD snooping and static multicast forwarding binding by ports for video surveillance application.

#### **802.1X security by MAC address**

MAC-based port authentication is an alternative approach to 802.1x for authenticating hosts connected to a port. By

authenticating based on the host's source MAC address, the host is not required to run a user for the 802.1x protocol. The RADIUS server that performs the authentication will inform the switch if this MAC can be registered in the MAC address table of switch.

#### **Protocol based VLAN; Subnet based VLAN**

The protocol-based VLAN processes traffic based on protocol. It filters IP traffic from nearby end-stations using a particular protocol such as IP, IPX, ARP or other Ethernet-types in a Hex value. Subnet based VLANs group traffics into logical VLANs based on the source IP address and IP subnet. The above features can help to build VLAN in the network mixed with managed and un-managed switch as to define packets to which VLAN group based on protocol or subnet.

#### **Editable configuration file; USB port for upload/download configuration**

The configuration file of Lantech T(P)GS-R5408MGT can be exported and edited with word processor for the following switches to configure with ease.

The USB port can upload/download the configuration from/to USB dongle.

#### **Event log & message; 2DI + 2DO; Factory default pin**

T(P)GS-R5408MGT provides 2DI and 2DO. When disconnection of the specific port was detected; DO will activate the signal LED to alarm. DI can integrate the sensors for events and DO will trigger the outside alarm and switch will send alert information to IP network with email and traps.

The factory reset pin can restore the setting back to factory default.

#### **Enhanced environmental monitoring for switch inside information**

The enhanced environmental monitoring can detect switch overall temperature, total power load, actual input voltage and current. It also can send the SNMP traps alert when abnormal.

#### **Optional smart bypass protection on dual 1G/2.5G ports\*\***

The bypass relay is set to bypass the switch to the next one when power is off to prevent network disruption. Lantech bypass caters to remain in bypass mode until the switch is completely booting up when power is back to avoid another network lost. Optional smart bypass (Up to two pairs) can be activated when switch encounters power failure or CPU hang. (-BT/-BBT model)

#### **Dual WVI input with max PoE budget and Inrush current protection**


The T(P)GS-R5408MGT WVI model accepts 16.8~137.5VDC dual input with galvanic isolation and PoE model can feed 54V output for PoE feeding with 80W budget. The inrush current on initial power up can be limited lower than 10 x nominal current.

#### **EN50155, EN45545-2; EN61373 compliance; High ESD protection**

T(P)GS-R5408MGT passed serious tests under extensive Industrial EMI and Safety standards. With EN45545-2 Fire & Smoke and EN50155 verification, the T(P)GS-R5408MGT is best switch for railway on-board/track side, vehicle and mining applications. For more usage flexibilities, T(P)GS-R5408MGT supports wide operating temperature from -40°C to 70°C. (85°C operation for 10min.)

## FEATURES & BENEFITS

- 8 10/100/1000T + 4 1G/2.5G Copper auto-sensing OS4 Ethernet Switch (Total 12 Ports Switch)
- PoE model: with 8/10 (incl.8 copper + 2 uplink 1G/2.5G copper) PoE 802.3af/at ports to feed power up to 30W for active mode operation (PoE budget 80W)
- Dual WVI input (16.8V~137.5VDC)
- Galvanic isolation from power input/Ethernet ports to system 1.5KV
- Back-plane (Switching Fabric): 36Gbps
- 16K MAC address table
- 10KB Jumbo frame
- PoE model: PoE management including PoE detection and scheduling for PD (power devices)
- User friendly UI, auto topology drawing, topology demo, complete CLI for professional setting
- Enhanced G.8032 Ring protection in 20ms for single ring
  - Support various ring/chain topologies, including enhanced ring & basic ring
  - Enhanced G.8032 ring configuration with ease
  - Cover multicast and data packets protection
- Supports IEEE 802.1p Class of Service, per port provides 8 priority queues Port base, Tag Base and Type of Service Priority
- IEEE 802.1d STP, IEEE 802.1w RSTP, 802.1s MSTP VLAN redundancy with 8 MSTI
- 4K 802.1Q VLAN, Port based VLAN, GVRP, QinQ, QoS
- Subnet VLAN and protocol VLAN
- Supports IEEE 802.1ab LLDP, Cisco CDP; LLDP info can be viewed via Web/ Console
- Support PXE to verify switch firmware with the latest or certain version
- DHCP server / client / DHCP Option 82 relay / DHCP Option 82 server; Port based DHCP server; DHCP Snooping; DHCP Option 66 ; basic IPv6 DHCP server
- Mac based DHCP server to assign IP address in DHCP network
- Bandwidth Control
  - Ingress packet filter and egress\* rate limit
  - Broadcast/multicast packet filter control
- Miss-wiring avoidance
  - LED indicator
- Node failure protection
  - Ensure the switches in a ring to survive after power breakout is back
  - The status can be shown in NMS when each switch is back
- System Event Log, SMTP\*\* alert and SNMP Trap for alarm support
- Security
  - SSL/SSH v2/INGRESS ACL L2/L3
  - MAC address table: MAC address entries/Filter/static MAC-Port binding
  - Remote Admin: IP address security management to prevent unauthorized intruder
  - TACACS+
  - Login Security: IEEE802.1X/RADIUS
  - HTTPS for secure access to the web interface
- Static multicast forwarding forward reversed IGMP flow with multicast packets binding with ports for IP surveillance application
- IGMP router port for Multicast protection
- MLD snooping for IPv6 Multicast stream
- IGMPv1,v2,v3 with Query mode for multi media
- Dual image firmware support
- Factory reset pin to restore setting to factory default
- Enhanced environmental monitoring for system actual input voltage, current, ambient temperature and total power load
- Supports 2DI/2DO (Digital Input/Digital Output)
- Configuration backup and restoration
  - Supports editable configuration file for system quick installation
  - USB port for upload/download the config
- TFTP/HTTP firmware upgrade
- Wide operation temperature: -40C~70C/-40F~158F (85°C operation for 10min.)
- EN45545-2 Fire & Smoke, EN50155 and EN61373 shock/vibration verification
- Diagnostic including Ping / ARP table / DDM information
- Enhanced Storm Control
- Optional L3Lite/L3\*/ETBN to be upgradable
- Built-in IEC 61375-3-4 ECN (Ethernet Consist Network) to work with IEC61375-2-5 TBN
- Optional smart bypass (Up to two pairs) (-BT/-BBT model)
- Inrush current protection
- IP54/IP67 aluminum housing with wall mount design

**DIMENSIONS (unit=mm)**

**SPECIFICATIONS**
**Hardware Specification**

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standards           | IEEE802.3 10Base-T Ethernet<br>IEEE802.3ab 1000Base-T<br>IEEE802.3x Flow Control and Back Pressure<br>IEEE802.3ad Port trunk with LACP<br>IEEE802.1d Spanning Tree<br>IEEE802.1w Rapid Spanning Tree<br>IEEE802.1s Multiple Spanning Tree<br>IEEE802.3ad Link Aggregation Control Protocol (LACP)<br>IEEE802.1AB Link Layer Discovery Protocol (LLDP)<br>IEEE802.1X User Authentication (Radius)<br>IEEE802.1p Class of Service<br>IEEE802.1Q VLAN Tag<br>IEEE802.3at/af Power over Ethernet |
| Switch Architecture | Back-plane (Switching Fabric): 36Gbps                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Mac Address         | 16K MAC address table                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Jumbo frame         | 10KB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Connectors          | 10/100/1000T: 8 x M12 8-pole X-coded with Auto MDI/MDI-X function<br>1G/2.5G Copper: 4 x M12 8-pole X-coded with Auto MDI/MDI function<br>Power Input connector: 1 x M12 4-pole Male A-coded<br>Reset/Console/USB : 1 x M12 8-pole A-coded<br>D/DIO: 1 x M12 5-pole A-coded                                                                                                                                                                                                                  |
| Network Cable       | 10Base-T: 2-pair STP Cat. 3, 4, 5/ 5E/ 6 cable<br>EIA/TIA-568 100-ohm (100m)<br>100Base-TX: 2-pair STP Cat. 5/ 5E/ 6 cable;<br>EIA/TIA-568 100-ohm (100m)<br>1000Base-T: 4-pair STP Cat5E/6 cable                                                                                                                                                                                                                                                                                            |

| LED                            | Per unit: Power 1 (Green), Power 2 (Green),<br>FAULT (Red); RM(Green)<br>10/100/1000T Ethernet port: Link/Activity (Green)<br>1G/2.5G copper: Link/Act (Yellow)<br>PoE : Link/Act (Green) (PoE model)                                                                     |                    |  |             |             |                    |            |                  |     |             |                    |     |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|--|-------------|-------------|--------------------|------------|------------------|-----|-------------|--------------------|-----|
| DI/DO                          | 2 Digital Input (DI) :<br>Level 0: -30~2V / Level 1: 10~30V<br>Max. input current:8mA<br>2 Digital Output(DO): Open collector to 80 VDC,<br>50mA                                                                                                                          |                    |  |             |             |                    |            |                  |     |             |                    |     |
| Operating Humidity             | 5% ~ 95% (Non-condensing)                                                                                                                                                                                                                                                 |                    |  |             |             |                    |            |                  |     |             |                    |     |
| Operating Temperature          | -40°C~-70°C / -40°F~158°F (85°C operation for 10min.)                                                                                                                                                                                                                     |                    |  |             |             |                    |            |                  |     |             |                    |     |
| Storage Temperature            | -40°C~85°C / -40°F~185°F                                                                                                                                                                                                                                                  |                    |  |             |             |                    |            |                  |     |             |                    |     |
| Power Supply                   | Dual DC input, 16.8VDC~137.5VDC                                                                                                                                                                                                                                           |                    |  |             |             |                    |            |                  |     |             |                    |     |
| PoE Budget (PoE model)         | <table border="1"><thead><tr><th>Input Range</th><th>Power Input</th><th>Maximal PoE Budget</th></tr></thead><tbody><tr><td>16.8~27VDC</td><td>Dual Power Input</td><td>80W</td></tr><tr><td>28~137.5VDC</td><td>Single Power Input</td><td>80W</td></tr></tbody></table> |                    |  | Input Range | Power Input | Maximal PoE Budget | 16.8~27VDC | Dual Power Input | 80W | 28~137.5VDC | Single Power Input | 80W |
| Input Range                    | Power Input                                                                                                                                                                                                                                                               | Maximal PoE Budget |  |             |             |                    |            |                  |     |             |                    |     |
| 16.8~27VDC                     | Dual Power Input                                                                                                                                                                                                                                                          | 80W                |  |             |             |                    |            |                  |     |             |                    |     |
| 28~137.5VDC                    | Single Power Input                                                                                                                                                                                                                                                        | 80W                |  |             |             |                    |            |                  |     |             |                    |     |
|                                | Higher PoE budget can be applied upon request. **                                                                                                                                                                                                                         |                    |  |             |             |                    |            |                  |     |             |                    |     |
| PoE pin Assignment (PoE model) | M12 port #1~#8 (-8 model)<br>M12 port #1~#8, #11~#12 (-10 model)<br><br>Support IEEE 802.3at/af End-point, Alternative A mode                                                                                                                                             |                    |  |             |             |                    |            |                  |     |             |                    |     |
| Power Consumption              | max. 42.8W exclude PoE load                                                                                                                                                                                                                                               |                    |  |             |             |                    |            |                  |     |             |                    |     |
| Dimensions                     | IP54/IP67 model: Aluminum case<br>390mm(W)x195mm(H)x112mm(D)                                                                                                                                                                                                              |                    |  |             |             |                    |            |                  |     |             |                    |     |

|                   |                                                                                                                                                                                                                                                                                                      |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Weight            | 3.8kgs                                                                                                                                                                                                                                                                                               |
| Installation      | Wall Mount Design                                                                                                                                                                                                                                                                                    |
| EMI & EMS         | FCC Part 15 Class A<br>EN61000-6-2<br>EN61000-6-4<br>CE EN55032 Class A<br>CE EN55024<br>CE EN61000-4-2 (ESD) Level 3<br>CE EN61000-4-3 (RS) Level 3<br>CE EN61000-4-4 (EFT) Level 3<br>CE EN61000-4-5 ED3 (Surge) Level 3<br>CE EN61000-4-6 (CS) Level 3<br>CE EN61000-4-8 (Magnetic field) Level 3 |
| Verifications     | EN50155/EN50121-3-2/EN50121-4 ;<br>EN45545-1, EN 45545-2 Fire & Smoke verification                                                                                                                                                                                                                   |
| Stability Testing | EN61373 (Shock and Vibration)                                                                                                                                                                                                                                                                        |
| MTBF              | TBC (standards: IEC 62380)                                                                                                                                                                                                                                                                           |
| Warranty          | 5 years                                                                                                                                                                                                                                                                                              |
| Bypass**          | Up to two pairs bypass module on 1G/2.5G Copper ports to pass to next switch in case of power failure and CPU hang                                                                                                                                                                                   |

### Software Specification

|                                   |                                                                                                                                                                                                                                                           |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Management                        | SNMP v1 v2c, v3/ Web/Telnet/CLI                                                                                                                                                                                                                           |
| SNMP MIB                          | RFC 1213 MIBII<br>RFC 1158 MIB<br>RFC 1157 SNMP MIB<br>RFC 1493 Bridge MIB*<br>RFC 1573 IF MIB<br>RFC 2674 Q-Bridge MIB*<br>RFC 2819 RMON MIB<br>Private MIB                                                                                              |
| PoE Management (PoE model)        | PoE Detection to check if PD hangs then restart the PD<br>PoE scheduling                                                                                                                                                                                  |
| Per Port PoE Status (PoE model)   | On/ Off, voltage, current, watts, temperature                                                                                                                                                                                                             |
| ITU G.8032                        | Support ITU G.8032 for Ring protection in less than 20ms for self-heal recovery (single ring enhanced mode)<br><br>Support basic single ring & enhanced ring<br>Enhanced G.8032 ring configuration with ease<br>Cover multicast & data packets protection |
| User friendly UI                  | <ul style="list-style-type: none"> <li>■ Auto topology drawing</li> <li>■ Topology demo</li> <li>■ Complete CLI for professional setting</li> </ul>                                                                                                       |
| Port Trunk with LACP              | LACP Port Trunk: 8 Trunk groups                                                                                                                                                                                                                           |
| LLDP                              | Supports LLDP to allow switch to advise its identification and capability on the LAN                                                                                                                                                                      |
| CDP                               | Cisco Discovery Protocol for topology mapping                                                                                                                                                                                                             |
| Enhanced Environmental Monitoring | System status for actual input voltage, current, total power load and ambient temperature to be shown in GUI and sent alerting if any abnormal status                                                                                                     |
| VLAN                              | Port Based VLAN<br>IEEE 802.1Q Tag VLAN (256 entries)/ VLAN ID (Up to 4K, VLAN ID can be assigned from 1 to 4096)<br>GVRP, QinQ, QoS<br>Protocol based VLAN<br>IPv4 Subnet based VLAN                                                                     |
| Spanning Tree                     | Supports IEEE802.1d Spanning Tree and IEEE802.1w Rapid Spanning Tree, IEEE802.1s Multiple Spanning Tree 8 MSTI                                                                                                                                            |
| Quality of Service                | The quality of service determined by port, Tag and IPv4 Type of service, IPv4 Differentiated Services Code Points - DSCP                                                                                                                                  |
| Class of Service                  | Support IEEE802.1p class of service, per port provides 8 priority queues                                                                                                                                                                                  |
| Remote Admin                      | Supports 10 IP addresses that have permission to access the switch management and to prevent unauthorized intruder                                                                                                                                        |
| Login Security                    | Supports IEEE802.1X Authentication/RADIUS                                                                                                                                                                                                                 |
| Port Mirror                       | Support 3 mirroring types: "RX, TX and Both packet"                                                                                                                                                                                                       |
| Network Security                  | Support 10 IP addresses that have permission to access the switch management and to prevent                                                                                                                                                               |

|                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                   | unauthorized intruder.<br>802.1X access control for port based and MAC based authentication/static MAC-Port binding<br>Ingress ACL L2/L3<br>SSL/SSH v2 for Management<br>HTTPS for secure access to the web interface<br>TACACS+ for Authentication                                                                                                                                                                                    |
| IGMP                              | Support IGMP snooping v1,v2,v3; Supports IGMP static route; 1024 multicast groups; IGMP router port ; IGMP query; GMRP                                                                                                                                                                                                                                                                                                                 |
| MLD Snooping                      | Support IPv6 Multicast stream                                                                                                                                                                                                                                                                                                                                                                                                          |
| Static multicast forwarding       | Static multicast forwarding forward reversed IGMP flow with multicast packets binding with ports for IP surveillance application                                                                                                                                                                                                                                                                                                       |
| Bandwidth Control                 | support ingress packet filter and egress* packet limit.<br>The egress* rate control supports all of packet type. Ingress filter packet type combination rules are Broadcast/Multicast/Flooded Unicast packet, Broadcast/Multicast packet, Broadcast packet only and all types of packet.<br>The packet filter rate can be set an accurate value through the pull-down menu for the ingress packet filter and the egress* packet limit. |
| Flow Control                      | Supports Flow Control for Full-duplex and Back Pressure for Half-duplex                                                                                                                                                                                                                                                                                                                                                                |
| System Log                        | Supports System log record and remote system log server                                                                                                                                                                                                                                                                                                                                                                                |
| Protection                        | <ul style="list-style-type: none"> <li>■ Miss-wiring avoidance</li> <li>■ Node failure protection</li> <li>■ Loop protection</li> </ul>                                                                                                                                                                                                                                                                                                |
| SNMP Trap                         | Up to 5 trap stations; trap types including: <ul style="list-style-type: none"> <li>● Device cold start</li> <li>● Authorization failure</li> <li>● Port link up/link down</li> <li>● DI/DO open/close</li> <li>● Typology change (ITU ring)</li> <li>● Power failure</li> <li>● Environmental abnormal</li> </ul>                                                                                                                     |
| PXE                               | PXE to verify switch firmware with the latest or certain version                                                                                                                                                                                                                                                                                                                                                                       |
| DHCP                              | Provide DHCP Client/ DHCP Server/DHCP Option 82/Port based DHCP; DHCP Snooping; DHCP Option 66 ; basic IPv6 DHCP server                                                                                                                                                                                                                                                                                                                |
| Mac based DHCP Server             | Assign IP address by Mac in DHCP network                                                                                                                                                                                                                                                                                                                                                                                               |
| DNS                               | Provide DNS client feature and can set Primary and Secondary DNS server                                                                                                                                                                                                                                                                                                                                                                |
| NTP/SNTP                          | Supports NTP/SNTP to synchronize system clock in Internet                                                                                                                                                                                                                                                                                                                                                                              |
| Firmware Update                   | Supports TFTP firmware update, TFTP backup and restore; HTTP firmware upgrade                                                                                                                                                                                                                                                                                                                                                          |
| Configuration upload and download | Supports editable configuration file for system quick installation; Support factory reset ping to restore all settings back to factory default                                                                                                                                                                                                                                                                                         |
| Enhanced Storm Control            | prevents traffic on a LAN from being disrupted by a broadcast, multicast, or unicast storm on one of the physical interfaces                                                                                                                                                                                                                                                                                                           |
| ECN                               | Complies with IEC 61375-3-4 (ECN) standard. The support of Ethernet Consist Network allows interconnection between end devices located in single consist of train and interoperability with IEC61375-2-5 (TBN).                                                                                                                                                                                                                        |
| Optional L3Lite/L3*/ETBN**        | Lantech OS4 are optional upgradable to L3 Lite/ L3* or ETBN communication protocols for future expansion. The optional L3Lite includes editable routing table, VRRP, Router-on-a-stick, Inter- VLAN routing. Optional ETBN complies with IEC61375-2-5 ETBN for Train Backbone Network. Detail SPEC upon request.                                                                                                                       |
| Diagnostic                        | Support Ping, ARP table and DDM information                                                                                                                                                                                                                                                                                                                                                                                            |
| Dual Image Firmware               | Support dual image firmware function                                                                                                                                                                                                                                                                                                                                                                                                   |

\*Future release

\*\*Optional



## ORDERING INFORMATION

All model packages include M12 caps. For optional bypass add -BT (one pair copper bypass); -BBT (two pairs copper bypass). For Coating add -C to end of model names.

- **TPGS-R5408MGT-8-54-WVI.....P/N: 8361-555**  
8 10/100/1000T + 4 1G/2.5G Copper M12 X-coded ; w/8 PoE at/af EN50155 OS4 Managed PoE Ethernet Switch ; 16.8V~137.5VDC dual input ; -40C~70C/-40F~158F ; IP54 housing w/ galvanic isolation
- **TPGS-R5408MGT-10-54-WVI.....P/N: 8361-5551**  
8 10/100/1000T + 4 1G/2.5G Copper M12 X-coded ; w/10 PoE at/af incl.2 1G/2.5G Copper EN50155 OS4 Managed PoE Ethernet Switch ; 16.8V~137.5VDC dual input ; -40C~70C/-40F~158F ; IP54 housing w/ galvanic isolation
- **TGS-R5408MGT-54-WVI.....P/N: 8361-5552**  
8 10/100/1000T + 4 1G/2.5G Copper M12 X-coded ; EN50155 OS4 Managed Ethernet Switch ; 16.8V~137.5VDC dual input ; -40C~70C/-40F~158F ; IP54 housing w/ galvanic isolation
- **TPGS-R5408MGT-8-67-WVI.....P/N: 8361-5553**  
8 10/100/1000T + 4 1G/2.5G Copper M12 X-coded ; w/8 PoE at/af EN50155 OS4 Managed PoE Ethernet Switch ; 16.8V~137.5VDC dual input ; -40C~70C/-40F~158F ; IP67 housing w/ galvanic isolation
- **TPGS-R5408MGT-10-67-WVI.....P/N: 8361-5554**  
8 10/100/1000T + 4 1G/2.5G Copper M12 X-coded ; w/10 PoE at/af incl.2 1G/2.5G Copper EN50155 OS4 Managed PoE Ethernet Switch ; 16.8V~137.5VDC dual input ; -40C~70C/-40F~158F ; IP67 housing w/ galvanic isolation
- **TGS-R5408MGT-67-WVI.....P/N: 8361-5555**  
8 10/100/1000T + 4 1G/2.5G Copper M12 X-coded ; EN50155 OS4 Managed Ethernet Switch ; 16.8V~137.5VDC dual input ; -40C~70C/-40F~158F ; IP67 housing w/ galvanic isolation

## OPTIONAL ACCESSORIES

### Software package

- **OS4 – L3L..... P/N: 9000-110**  
OS4 software platform with Layer 3 Lite functions (please check Lantech software data sheet for details)
- **OS4 – IEC61375-2-5 ..... P/N: 9000-111**  
OS4 software platform with IEC-61375-2-5 ETBN (Ethernet Train Backbone Networks) function (please check Lantech software data sheet for details)
- **OS4 – L3\*..... P/N: 9000-112**  
OS4 software platform with Layer 3 functions incl. L3L (please check Lantech software data sheet for details)
- **OS4 – R-NAT ..... P/N: 9000-113**  
OS4 software platform with R-NAT function (please check Lantech software data sheet for details)

### M12 Connector & Cable

#### Connector

- **ECONM12-04A(F)-C-180** 4 pin M12 (Female) A-coded 180 degree crimp type connector for power supply
- **ECONM12-08A(M)-180** 8 pin M12 (Male) A-coded 180 degree crimp type connector for reset/console/USB
- **ECONM12-05A(M)-C-180** 5 pin M12 (Male) A-coded 180 degree crimp type connector for DI/DO
- **ECONM12-08X(M)-SPEEDCON** 8 pin M12 (Male) X-coded 180 degree crimp type connector for data, Ethernet CAT6A (10G), shielded, SPEEDCON

#### Cable

- **ECONM12-4P(F)1.5M CABLE** 4 pin M12 (Female) A-coded 90 degree cable for power supply, 150cm
- **ECONM12-08M2-CONSOLE** 8 pin M12 (Male) A-coded 180 degree to RS232 cable for console, 150cm
- **ECABM12X83MSTP** 8 pin M12 (Male) X-coded 180 degree RJ45 STP cable for data, shielded, 300cm

#### Others

- **M12 to USB interface adapter** 8 pin M12 (Male) A-coded 180 degree M12 to USB 2.0 interface adapter, 8cm
- **USB 2.0 Ethernet Adapter** USB 2.0 to RJ45 Ethernet Adapter
- **ECONM12-08(M) TO DB9+USB2.0-1.5M CABLE** 8 pin M12 (Male) A-coded 180 degree M12 to USB2.0 to DB9 (Female) cable, 150cm

**Lantech Communications Global Inc.**  
[www.lantechcom.tw](http://www.lantechcom.tw)  
[info@lantechcom.tw](mailto:info@lantechcom.tw)

© 2022 Copyright Lantech Communications Global Inc. all rights reserved.  
 The revise authority rights of product specifications belong to Lantech Communications Global Inc.  
 In a continuing effort to improve and advance technology, product specifications are subject to change without notice.