



BFC-1232

12.1" 6th Gen Intel® ULT Core™ Processor Fanless Full Flat Multi-Touch Panel PC

Onboard 6th Gen Intel® ULT Core™ i5 6300U 2. BGA Processor

Full Flat Front Panel with Projected Capacitive To Supports Multi Touch

2 x Intel® Gigabit Ethernet, 5.1-CH Audio

1 HDMI, 6 USB 3.0, 3 COM

Fanless System & VESA Compliance

Wide Voltage +12V ~ +26V Input, ErP Power

Timer-Power-On

Front Side IP65 Dust and Water Proof



System Information-

Processor	6th Gen Intel® Core™ i5-6300U, 2-Core, 2.4GHz processor
System Memory	1 x 260-Pin DDR4 2133MHz SO-DIMM up to 16 GB
I/O Chipset	EC ITE IT8528E
Watchdog Timer	H/W Reset, 1sec. ~ 65535min. and 1sec. or 1min./step
H/W Status Monitor	Monitoring CPU & System Temperature and Voltage
SBC	EBM-SKLU

Expansion

Expansion	1 x Mini PCIe Supports mSATA 1 x Mini PCIe Supports SIM Card
------------------	---

Storage

Storage	1 x 2.5" Drive Bay
----------------	--------------------

Panel

LCD Size	12.1", 4:3
Display Type	XGA
Resolution	1024x768
Pixel pitch	0.240mm (H) x 0.240mm (V)
Luminance	600cd/m2
Contrast ratio	1000
Viewing angle	89 (U), 89 (D), 89 (L), 89 (R)
Response time	11ms
Backlight	LED
Touch Type	Projective Capacitive support up to 10 points multi-touch
Touch Light Transmission	89 %
Touch Controller	USB touch (EETI)

I/O

USB Port	4 x USB 3.0
COM Port	2 x RS-232/422/485 1 x RS-232
HDMI	1x HDMI

Display

Graphic Chipset	Intel® Skylake U SoC integrated Graphics
Spec. & Resolution	HDMI:Max. resolution 4096x2304@ 24Hz

Audio

Audio Codec	Realtek ALC233 supports 2.1-CH
Audio Interface	Line-Out and Amp.

Certifications

Certification Information	CE / FCC Class B
----------------------------------	------------------

Ethernet

LAN Chipset	1 x Intel® I210AT 1 x Intel® I219LM
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	2 x RJ-45

Power Requirement

DC Input +12V ~ +26V**DC Input Connector** Customized

W

**Power Mode** AT/ATX
Adapter Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A Adapter)**.Mechanical & Environmental****Operating Temperature** 0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature -10°C ~ 50°C (14°F ~ 122°F)
Operating Humidity 5% ~ 90% Relative Humidity, Non-condensing
Dimension (W x L x H) 292.9 x 225.4 x 50.14mm
Weight 3.8Kgs
Vibration Test With SSD/mSATA : 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
Shock Test With CF/SSD : 10Grms, IEC 60068-2-27, Half Sine, 11ms
System Fan Fanless
Construction - Front Silver Aluminum
Construction - Rear Black**.Software Support****OS Information** Win 7
Win 10
Linux**.Ordering Information****Ordering Information** BFC-1232-630-A1R
6th Gen Intel® ULT Core i5 6300U 2.4GHz/2LAN/3COM/6USB/12~26V Input/12V Adaptor

W