


GS480-01

HPC Server - 4U DP 8 x Gen4 GPUs



AMD
INSTINCT



Product Highlight

- Up to 8 x PCIe Gen4 GPGPU cards
- Dual AMD EPYC™ 7002 series processor family
- 8-Channel RDIMM/LRDIMM DDR4, 32 x DIMMs
- 2 x 1Gb/s BASE-T LAN ports (Intel® I350-AM2)
- 1 x dedicated management port
- 2 x 2.5" Gen4 U.2, 8 x 2.5" SATA hot-swap HDD/SSD bays
- 8 x FHFL Gen4 expansion slots for GPU cards
- 1 x FHFL PCIe Gen4 x16 expansion slot
- Aspeed® AST2500 remote management controller
- 3 x 80 PLUS Platinum 2200W redundant PSU

Specification

Dimensions	4U (W448 x H176 x D800 mm)	Backplane I/O	2 x NVMe and 8 x SATA ports
Motherboard	MZ52-G41	TPM	1 x TPM header with SPI interface Optional TPM2.0 kit: CTM010
CPU	AMD EPYC™ 7002 series processor family Dual processors, 7nm, Socket SP3 Up to 64-core, 128 threads per processor TDP up to 225W, cTDP up to 280W	Power Supply	3 x 2200W 80 PLUS Platinum power supply
Chipset	System on Chip	System Management	Aspeed® AST2500 management controller AccelStor Management Console (AMI MegaRAC SP-X)
Memory	32 x DIMM slots, DDR4 memory supported only 8-Channel memory per processor architectures RDIMM/LRDIMM modules up to 128GB supported Memory speed: Up to 3200/ 2933 MHz	OS Compatibility	Windows Server 2016 / 2019 RHEL 7.6 (x64) / 8.0 (x64) or later SLES 12 SP4 (x64) / 15 SP1 (x64) or later Ubuntu 16.04.6 LTS (x64) / 18.04.3 LTS (x64) / 20.04 LTS (x64) VMware ESXi 6.5 EP15 / 6.7 Update3 / 7.0 or later Citrix Hypervisor 8.1.0 or later
LAN	2 x 1Gb/s BASE-T LAN ports (Intel® I350-AM2) 1 x 10/100/1000 management LAN	Weight	Net Weight: 29.5 kg / Gross Weight: 47.5 kg
Video	Integrated in Aspeed®AST2500 2D Video Graphic Adapter with PCIe bus interface 1920x1200@60Hz 32bpp	System Fans	12 x 60x60x38mm (21,700rpm)
Storage	2 x 2.5" Gen4 U.2, 8 x 2.5" SATA hot-swappable HDD/SSD bays NOTE: non-supported SAS devices	Operating Properties	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
SATA	Supported	Packaging Content	1 x GS480-01 2 x CPU heatsinks 1 x Rail kit
SAS	N/A		
Expansion Slots	8 x PCIe x16 slots (Gen4 x16) for GPUs 1 x FHFL PCIe Gen4 x16 expansion slot in rear side* * Non-supported SAS Card with internal cable due to cable routing limitation		
Internal I/O	1 x TPM header, 1 x Front panel header		
Front I/O	2 x USB 3.0, 1 x VGA, 2 x RJ45, 1 x MLAN		
Rear I/O	-		



Learn more about AccelStor HPC solutions, visit www.accelstor.com

* All specifications are subject to change without notice. Please visit our website for the latest information.

* Intel, the Intel logo, Xeon, and other Intel marks are trademarks of Intel Corporation or its subsidiaries.

* All other brands, logos and names are property of their respective owners.

© 2020 AccelStor Technologies Ltd. All rights reserved.