

XF3ES-B Series - 75" UHD 3,000nits Open-frame High Brightness Display

75XF3ES-B

Key Features

- Brightness : 3,000 cd/m² (Typ.)
- Life Time : 50,000 hours
- Bezel : 11.8 mm (Even bezel)
- Depth : 128.9 mm
- Interface : HDMI (2)/ DP/ DVI-D/ USB/ RJ45/ RS232C/ IR/ External speaker out



All Spec

PANEL

Screen Size (Inch)	Native Resolution
75" (74.52" Measured Diagonal)	3,840 x 2,160 (UHD)
Brightness	
3000	

MECHANICAL SPECIFICATION

Bezel Width	Weight (Head)
11.8 mm (Even)	37.5 kg
Packed Weight	Monitor Dimensions (W x H x D)
47.0 kg	1,675.2 x 953.6 x 128.9 mm
Carton Dimensions (W x H x D)	
1,816 x 1,106 x 285 mm	

ENVIRONMENT CONDITIONS

Operation Temperature	Operation Humidity
0°C to 50°C (w/o Direct Sunlight, Direct Sunlight in Cooling System), 0°C to 40°C (Direct Sunlight)	10 % to 80 %

POWER

Power Supply	Power Type
100-240 V~, 50/60 Hz	Built-In Power

POWER CONSUMPTION

Max.	Typ.
700W	620W (Full White) 353W (IEC 62087)

CERTIFICATION

Safety	EMC
IEC 60950-1 / EN 60950-1 / UL 60950-1	FCC Class "A" / CE / KC
ERP / Energy Star	
Yes (EU Only) / No	

ACCESSORY

Basic	Optional
Remote Controller, Power Cord, HDMI Cable, IR Extension Kit, Manual (ESG&EIG)	Wi-Fi Dongle (AN-WF500)