

SPEC_ITEM_LOCAL	
Display	Diagonal Size
	Panel Type
	Resolution
	Pixel Pitch (HxV)
	Brightness (Typ)
	Contrast Ratio
	Viewing Angle (H/V)
	Response Time
	Color Gamut
	Glass Haze
	H-Scanning Frequency
	Maximum Pixel Frequency
	V-Scanning Frequency
	Contrast Ratio (Dynamic)
	Operation Time Support
Connectivity	HDMI In
	DP In
	DVI In
	Version of HDMI
	Version of DP
	Version of HDCP
	USB
	IR In
	Audio In
	Audio Out
Power	Video Out
	RS232 In
	RS232 Out
Dimension	RJ45 In
	Power Supply
	Power Consumption (On Mode)
Weight	Power Consumption (Sleep Mode)
	Set Dimension (WxHxD) (mm)
Operation Conditions	Package Dimension (WxHxD) (mm)
	Set Weight (kg)
	Package Weight (kg)
Mechanical Specification	Temperature (°C)
	Humidity (%)
	VESA Mount (mm)
	Bezel Width
Optional Feature	Bezel Color
	Frame Material
Certification and Compliance	Mount
	EMC
	Safety

Value
55"
IPS
1,920 x 1,080
0.63x0.63
MAX 700 nit
1,000:1
178/178
8ms
72 %
28 %
57.3kHz ~ 70kHz
78MHz
47Hz ~ 63Hz
140,000:1
24/7
2
1
1
2
1.2
2.2
1
Yes
Yes
Stereo Mini Jack
Yes
Yes
Stereo Mini Jack
Yes
AC100-240V 50/60Hz
250 W
0.5 W
1212.2 x 683.0 x 70.4 mm
1398 x 844 x 257 mm
19.5 kg
27.1 kg
0°C ~ 40°C
10 ~ 90%
600 x 400 mm
B2B : 1.74mm (Panel Bezel to Panel Bezel), 1.3mm(U/L), 0.44mm(R/B) A2A : 2.49mm (Active area to Active area),
Black
Glossy
Yes
FCC (USA) Part 15, Subpart B Class B CE (Europe) : EN 55032:2015+A11:2020 / EN 55035:2017+A11:2020 / EN
CB (Europe) : IEC62368-1/EN62368-1 CCC (China) : GB 4943.1-2011 (Singapore) : PSB+IEC62368-1NOM (Mexico)

IEC 61000-3-2:2019 / EN 61000-3-3:2013+A1:2019 VCCI (Japan) : VCCI-CISPR32 : 2015 KC (Korea) : KS C
co) : Tunerless : NOM-019-SCFI-1998IRAM (Argentina) : IRAM+IEC62368-1 SIRC (Saudi Arabia) : SASO+

9832 / KS C 9835 RCM (Australia/ Newzealand) : AS/NZS CISPR32:2015 CCC (China) : GB/T 9254-2008, G
-IEC62368-1 BIS (India) : IEC60950-1 / IS13252KC (Korea) : K 60950-1EAC (Russia) : EAC+IEC60950-1 BSI

MI (Taiwan) : BSMI+IEC60950-1 RCM(Australia) : IEC62368-1/AS/NZS 62368-1 UL (USA) : cUL62368-1 CS

SA (Canada) : cUL