


EMX-W880P

Intel® Core™ Ultra Processors, Mini ITX
Motherboard with Intel® W880 Chipset



Product Features

- LGA 1851 Socket Supports Intel® Core™ Ultra Processors with Intel® W880 Chipset (Max. TDP at 125W)
- 2 x DP++(one from Type C), 1 x HDMI 2.1b, 1 x eDP or LVDS
- 1 x Intel® i226LM, 2 x Intel® i226V 2.5 Gigabit, 1 x Intel® i210AT controller
- 1 x M.2 (2230) E-Key, 2 x M.2 (2242/2280) M-Key
- ATX Power
- 2 x 262-Pin DDR5 6400MHz Dual Channel CSO-DIMM Socket Supports Up to 96GB
- 1 x PCIe x16 (Gen5)
- 4 x USB 3.2 Gen2, 4 x USB 3.2 Gen1, 2 x USB 3.2 Gen2, 2 x USB 2.0
- 5 x COM

Specification

System Information	
Processor	LGA 1851 Socket Supports Intel® Core™ Ultra Processors (Max. TDP at 125W)
Platform Controller Hub	Intel® W880 Chipset
System Memory	2 x 262-Pin DDR5 6400MHz Dual Channel SO-DIMM Socket Supports Up to 96GB
I/O Chipset	uBMC IT5792(IPMI) or equivalent
Watchdog Timer	H/W Reset, 5~255 Seconds/5~255 Minutes
BIOS	AMI uEFI BIOS, 256Mbit SPI Flash ROM
H/W Status Monitor	CPU Temperature Monitoring Voltage Monitoring CPU Fan Speed Control
TPM	Onboard NuvoTon NPCT760AABYX support TPM2.0
Board	Mini ITX

Expansion

Expansion	1 x PCIe x16 Gen5 (from CPU) support graphic & NVMe 1 x M.2 (2230) E-Key, Support WiFi Module with PCIe x2 Gen4 & USB 2.0 1 x M.2 (2242/2280) M-Key, Support PCIe x4 Gen4 & SATA signal SSD 1 x M.2 (2280) M-Key, Support PCIe x4 Gen4 SSD
-----------	---

Display

Graphic Chipset	Intel® Xe LPG graphics architecture CPU integrated
Spec. & Resolution	1 x DP 2.1: 7680 x 4320@60Hz 1 x USB4 Type C at I/O with DP-alt mode 1 x HDMI 2.1: 8K@60Hz 1 x LVDS: 1920 x 1080@60Hz Dual channel 18/24-bits LVDS (Chrontel CH7513A-BF eDP to LVDS) Or 1 x eDP 1.4b 1920 x 1080@60Hz (2 Lanes)
Multiple Display	4 Independent Displays
LVDS	Dual Channel 18/24-bits LVDS (Chrontel CH7513A-BF eDP to LVDS) or 1 x eDP 1920 x 1080@60Hz (2 Lanes)

Audio

Audio Codec	Realtek ALC888S HD Audio Decoding Controller
Audio Interface	Support Line-out & Mic-in & Front Audio Pin-header
Audio Amplifier	2 x 3W 4Ω Amplifier

Ethernet

LAN Chipset	1 x Intel® i226LM, 2 x Intel® i226V 2.5 Gigabit, 1 x Intel® i210AT Controller
Ethernet Interface	100/1000/2500 Base-Tx GbE compatible Gigabit Ethernet
LAN Port	4 x RJ-45

Software Support

OS	Windows 11, Linux
----	-------------------

Certification

Certification Information	CE, FCC, RoHS Compliant
---------------------------	-------------------------

I/O

USB	4 x USB 3.2 Gen2 at I/O 4 x USB 3.2 Gen1 at I/O 2 x USB 3.2 Gen2 by pin header 2 x USB 2.0 by pin header
COM Port	3 x RS232 2 x RS232/422/485
SATA	2 x SATA III

RAID	Support RAID 0, 1
DIO	1 x 16-bit GPIO
Mechanical & Environmental	
Operating Temp.	0~55°C (32~131°F) w/HDD/SSD, ambient 0.5m/s air flow
Storage Temp.	-40 ~ 75°C (-40 ~ 167°F)
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Weight	0.88lbs (0.4Kgs)
Power Requirement	+12V / +5V / 5VSB /+3.3V /-12V
Power Mode	AT/ATX (Default Setting: ATX)
Dimension (L x W)	6.7" x 6.7" (170mm x 170mm)
Ordering Information	
Ordering Information	EMX-W880P-A1R Intel® Core™ Ultra Processors Mini ITX motherboard