



Digital Signage Display

ULO2703

27" TFT LCD, 500 nits LED Backlight, 1920x1080

Brightness 500 nits

LED Backlight

Low Power Consumption

BL MTBF: 50,000 hours

Model Name	ULO2703-IHB	ULO2703-IHT
Description	27" TFT LCD, 500 nits LED Backlight, 1920x1080, Projected Capacitive Touch	
Screen Size	27"	
Display Area (mm)	597.888 (H) x 336.312 (V)	
Brightness	500 cd/m2	
Resolution	1920x1080	
Aspect Ratio	16 : 9	
Contrast Ratio	1400 : 1	

Pixel Pitch (mm)	0.3114 (H) x 0.3114 (V)	
Pixel Per Inch (PPI)	82	
Viewing Angle	176°(H),176°(V)	
Color Saturation (NTSC)	84%	69%
Display Colors	16.7M	
Response Time (Typical)	14ms	
Panel Interface	LVDS	
Input Interface	HDMI, DP , USB (Touch Interface)	
Input Power	DC12V	
Power Consumption	25W	
OSD Key	4 Keys (Power Switch, Menu, +, -)	
OSD Control	Brightness, Color, Contrast, Auto Turing, H/V Position...etc	
Dimensions (mm)	632.6 x 370.8 x 48.8 mm	649 x 387.5 x 53 mm
Bezel Size(U/B/L/R)	17.2/17.2/17.4/17.4 mm	25.6/25.6/25.6/25.6 mm
Mounting	100 x 100 mm , 300 x 200 mm	
Weight (Net)	7.18 Kg	9.1 Kg
Operating Temperature	0 °C ~ 50 °C	
Storage Temperature	-20 °C ~ 60 °C	

