

PPC-2164PW/RW

21.5" Front Panel IP54 Panel PC with Intel® Celeron® J6412 Processor

Applications

- HMI Solution
- Embedded Panel PC on the chassis
- Digital Transformation
- ATM / Self-service / Kiosk Application
- Industrial Automation

Features

- 21.5" 1920 x 1080 Resolution, 250nits Panel
- Intel® Celeron® J6412 onboard Processor
- SECC Front Panel + Aluminum Back Cover
- IP54 Rated Front Panel
- Support Projected Capacitive and Resistive Touchscreen
- Support VESA and Panel Mounting



Ordering Information

Part No.	Description
PPC-2164PW	21.5" 16:9 (1920 x 1080) FHD, 250nits, P-CAP Touch, SECC, Intel® Celeron® J6412, 2 x GbE, 2 x HDMI, 4 x USB3.2, Line-Out, 12~36VDC (2-pin Terminal Block)
PPC-2164RW	21.5" 16:9 (1920 x 1080) FHD, 250nits, 5-wire Resistive Touch, SECC, Intel® Celeron® J6412, 2 x GbE, 2 x HDMI, 4 x USB3.2, Line-Out, 12~36VDC (2-pin Terminal Block)

Packing List

Description
1 x PPC-2164PW/RW


Optional Items

Part No.	Description
EA-PS-60W12VTB2xx-0211	Adapter AC/DC 12V 5A 60W with 2-pin Terminal Block Plug 5.0mm Pitch
27-x301000003-CA	Power Cord, 3-pin US Type, 180 cm
27-x301010005-CA	Power Cord, 3-pin EU Type, 180 cm
EA-AWD-4G003xxxxx-0011	4G (LTE) EG25-G + 2 Antennas, Full Size (for Global)
EA-AWD-WF003x01x1-0011	Wi-Fi 802.11 a/b/g/n/ac/BT4.0 (2T2R) + 2 Antennas (Dual Band), Half Size
EA-AWD-WFM2BT52TR-0011	Wi-Fi 802.11 a/b/g/n/ac/BT5.0 (2T2R) + 2 Antennas (Dual Band), M.2 2230 Type

Specifications

Model		PPC-2164PW	PPC-2164RW
Processor System	CPU	Intel® Celeron® J6412 Processor	
	Frequency	up to 2.60GHz	
	BIOS	UEFI	
	TPM	fTPM	
Memory	Technology	Dual Channel DDR4 3200MHz (un-buffered and non-ECC)	
	Max. Capacity	Support up to 32GB	
	Type	2 x 260-pin SO-DIMM	
Panel	Panel Type	21.5" FHD LCD	
	Aspect Ratio	16:9	
	Resolution	1920 x 1080	
	Brightness	250cd/m ²	
	Color	16.7M	
	Contrast Ratio	5000:1	
	Viewing Angle	178 (H) x 178 (V)	
	Backlight MTBF (typ.)	30,000Hrs	
Touchscreen	Touchscreen Type	Projected Capacitive (P-CAP)	5-wire Resistive
	Surface Hardness	7Mohs	3Mohs
	Transparency	90% (±3%)	80% (±3%)
I/O Interface	Ethernet	2 x GbE LAN Ports (Intel® I211-AT)	
	HDMI	2 x HDMI 2.0, Max Resolution 4096 x 2160	
	Serial Port	Optional for 2 x RS232/422/485	
	USB	4 x USB3.2 Gen1	
	Audio	1 x Line-out	
Storage	2.5" SSD/HDD	Internal 1 x 2.5" SSD/HDD	
	M.2	Internal 1 x M.2 2280 M-Key (PCIe x2, SATA)	
Expansion	Mini-PCIe	1 x Full-Size Mini-PCIe with SIM slot (PCIe, USB2.0 and SIM)	
	M.2	1 x M.2 2280 M-Key (PCIe x2, SATA)	
Power	Power Mode	AT/ATX	
	Power Supply Voltage	12~36V DC Input	
	Power Connector Type	1 x DC Power Connector, 1 x 2-pin Terminal Block	
Environment	Operating Temperature	-20C ~ +60°C	
	Storage Temperature	-30C ~ +70°C	
	Humidity	10% ~ 95%, Non-condensing	
	Vibration	2.16Grms, 5 - 500Hz, 0.5hr/axis	
	Shock	20G, half sine, 11ms	
General	Certification	CE/FCC Class A	
	Ingress Protection	Front Panel IP54	
	Material	SECC Front Panel + Aluminum Back Cover	
	Mounting	VESA (100 x 100mm) / Panel	
	Dimensions (W x H x D)	580.6 x 372.1 x 58.5mm	
	Net Weight	6.99kg	
	Operating System	Windows 10 IoT, Windows 11 (IoT/Professional), Linux	

Dimensions



Viewing

